WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 69164
Permit No.
Basin 083

NOTICE OF INTENT NO. 33243

1. OWNER Mike Browning
MAILING ADDRESS 5515 Wedekind Rd.
Sparks NV 89431

ADDRESS AT WELL LOCATION 21945 Adobe
Virginia City Highlands
Lot 25 Block G

2. LOCATION NW ¼ NW ¼ Sec. 33 T 18 N N/S R 21 E.ast Storey County
PERMIT NO. (Issued by Water Resources) 03-045-48 (Parcel No.) Virginia City Highlands (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown Clay		0	10	10
Brown D.G.		10	20	10
Brown Sticky Clay		20	40	20
Gray clay stone soft		40	80	40
Gray clay		80	100	20
Gray & black clay stone		100	120	20
Black &gray gravel	X	120	130	10
Multi colored valcanic				
Rock med. hard		130	165	35
Weatherd Granite		165	175	10
Multi colored volc.	X	175	205	30
Green & black clay				
Stone		205	220	15
T.D. 220'				

Date started March 19, 1997
Date completed March 21, 1997

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50		2 hours

8. WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 220 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8 Inches		0 Feet	50 Feet
8 1/2 Inches		50 Feet	220 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.92	.188	+1½	220

Perforations:
Type perforation Factory Sawed
Size perforation 3/32 X 3
From 180 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100'
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 220 feet to 100 feet

9. WATER LEVEL
Static water level 45 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A.S.A.P. Pump & Well Service, Inc. (Contractor)
Address 1800 ½ Frazer Ave (Contractor)
Sparks NV 89431
Nevada contractor's license number issued by the State Contractor's Board 35387-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1509T-1
Signed Larry Welch (By driller performing actual drilling on site or contractor)
Date 3-24-97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627