WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 69173
Permit No.
Basin 90

NOTICE OF INTENT NO. 38392

1. OWNER Shell (S-9)
MAILING ADDRESS 898 N. Tahoe Blvd Incline Village - Nev
ADDRESS AT WELL LOCATION Northside Janager 200 ft west of Village Blvd Incline Village - Nev

2. LOCATION SW ¼ NE ¼ Sec. 15 T. 16 N/S R. 18 E. Washoe County
PERMIT NO. NA (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Percussion Hammer

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| 60% Fine to med Sand | | 0 | | |
| 15% silt 25% Fine | | | 33 | |
| Coarse gravels | | | 33 | 33 |
| 70% Fine to Coarse | | 33 | | |
| Sand 30% Fine to | | | | |
| Coarse gravel | | | 64 | 31 |
| 65% Fine to Coarse | | 64 | | |
| Sand 30% Fine to | | | | |
| Coarse gravel 5% | | | | |
| Boulders | | | 80 | 16 |
| 60% silt to coarse | | 80 | | |
| Sand 30% Fine to | 84 | | | |
| Coarse gravel 10% | | | | |
| Boulder | | | 109 | 29 |

97 OCT -6 PM 12:45

Date started 9/19, 1997
Date completed 9/19, 1997

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| NONE | | |

8. WELL CONSTRUCTION
Depth Drilled 109 Feet Depth Cased 109 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 10" Inches | 0 Feet | 109 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4" | PVC | Sch. 40 | 0 | 74 |

Perforations:
Type perforation slot
Size perforation .020
From 74 feet to 109 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 68'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 71 feet to 109 feet

9. WATER LEVEL
Static water level 84.2 feet below land surface
Artesian flow NA G.P.M. NA P.S.I.
Water temperature NA °F Quality NA

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Layne Christensen (Contractor)
Address 11001 Etiwanda Ave (Contractor)
Fontana - CA 92337
Nevada contractor's license number issued by the State Contractor's Board #0019101
Nevada driller's license number issued by the Division of Water Resources, the on-site driller #1468
Signed Steve Johnson
By driller performing actual drilling on site or contractor
Date 10/1/97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627