WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

15DAD

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 092206
Permit No. 93
Basin I

NOTICE OF INTENT NO. 37088

1. OWNER: RICHARD FAULKNER
MAILING ADDRESS: 1275 Klippe, Unit #17, Sparks, Nevada 89431
ADDRESS AT WELL LOCATION: 25 Prarie Way, Reno, Nevada 89506

2. LOCATION: NSE ¼ SE ¼ Sec. 15 T 22N N/S R 19 E Washoe County
PERMIT NO. (Issued by Water Resources) 079-490-12 (Parcel No.) Antelope Valley Fairhock Estates #2 (Subdivision Name) page-1

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Decomposed granite				
mixed w/brown clay		2	6	4
Brown sandy clays some				
decomposed granite		6	38	32
Decomposed granite		38	86	48
Weathered granite		86	188	102
Soft zone (NO WATER)		188	197	9
Weathered granite		197	211	14
Rusty brown soft sand		211	228	17
Weathered granite		228	248	20
Soft zone & fracture	X	248	393	145
Weathered granite		393	300	7

Date started 9-22-97, 19
Date completed 9-23-97, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	300 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	300

Perforations:
Type perforation: factory sawed slot
Size perforation: 3/32 x 3 x 5 around
From 255 feet to 295 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal: 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 300 feet

9. WATER LEVEL
Static water level 198 feet below land surface
Artesian flow G.P.M. 15 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name: WAYNE DRILLING, INC. (Contractor)
Address: P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board: 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 923

Signed: Gary Pettelman (By driller performing actual drilling on site or contractor)
Date: September 25, 1997

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627