WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY
GMWCX3
PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 69530
Permit No.
Basin 66

NOTICE OF INTENT NO. 15790

1. OWNER Pinson Mining Company
MAILING ADDRESS P.O. Box 129
Winnemucca NV. 89446

ADDRESS AT WELL LOCATION 20 miles Northeast Of Golconda N.V. AT Pinson Mine

2. LOCATION SW ¼ SE ¼ Sec. 29 T. 38 N/S R. 42 E. Humboldt County
PERMIT NO. N/A (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	145'	145'
Shale		145'	495'	350'
Neat Cement		0	10'	10'
¾" Hole Plug		10'	218'	208'
Abantonite		218'	267'	49'
10/20 Silica Sand		267'	346'	79'
@ Neat Cement		346'	495'	149'

Date started 10-31-, 19 97
Date completed 11-5-97, 19 97

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
245'	9		5 min.
305'	20		5 min.
345'	30		5 min.

8. WELL CONSTRUCTION
Depth Drilled 495' Feet Depth Cased 318' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12"	Inches	0	Feet	40'	Feet
6¾"	Inches	40'	Feet	495'	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8⅝"		¼" Wall	+2	40'
2½"		SCH 80	+2	318'

Perforations:
Type perforation Horezontel Slot
Size perforation 0.02 Slotes
From 278' feet to 318' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 10'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 267' feet to 346' feet

9. WATER LEVEL
Static water level 213.25 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality Clean

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co. (Contractor)
Address P.O. Box 2748 (Contractor)
Elko Nevada 89803
Nevada contractor's license number issued by the State Contractor's Board #0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1786
Signed Craig Dines (By driller performing actual drilling on site or contractor)
Date 11-6-97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627