

DIVISION OF WATER RESOURCES

Log No. 89568  
Permit No. 84  
Basin. 1  
NOTICE OF INTENT NO. 37122

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

22 DCAA

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER RICHARD & B.J. PAGANO ADDRESS AT WELL LOCATION 4400 Amy Road corner Wilcox Ranch Road  
MAILING ADDRESS 5961 Spring Valley Road Sparks, Nevada 89433 Reno, Nevada 89510  
2. LOCATION SW 1/4 SE 1/4 Sec. 22 T. 22N N/S R. 21 E Washoe County  
PERMIT NO. 66418-66411 Issued by Water Resources 077-140-20 Parcel No. Palomino Valley Unit 1 Subdivision Name 22-2-1-12

3. WORK PERFORMED  
 New Well  Replace  Recondition  Deepen  Abandon  Other  
4. PROPOSED USE  
 Domestic  Municipal/Industrial  Irrigation  Monitor  Test  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Top soil		0	1	1
Sand & gravel		1	16	15
Brown sandy clay		16	31	15
Sand & gravels		31	33	2
Brown sandy clay		33	71	38
Sand & gravel (NO WATER)		71	76	5
Brown sandy clay		76	116	40
Brown sandy clay with volcanic gravels		116	131	15
Soft zone (NO WATER)		131	136	5
Brown sandy clay		136	153	17
Soft zone, granite sands		153	155	2
Brown sandy clays with volcanic gravels, granite sands		155	232	77
Soft zone, sand and gravels	X	232	243	11
Brown sandy clay, volcanic gravels		243	262	19

8. WELL CONSTRUCTION  
Depth Drilled 262 Feet Depth Cased 262 Feet  
HOLE DIAMETER (BIT SIZE)  
From 10 Inches To 0 Feet 262 Feet  
Casing Schedule  
Size O.D. (Inches) 6 5/8 Weight/Ft. (Pounds) .188 Wall Thickness (Inches) 0 From (Feet) 262 To (Feet)  
Perforations:  
Type perforation factory sawed slot  
Size perforation 3/32 x 3 x 5 around  
From 217 feet to 257 feet  
Surface Seal:  Yes  No Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
Depth of Seal 50 feet  
Placement Method:  Pumped  Poured  
Gravel Packed:  Yes  No  
From 50 feet to 262 feet

Date started 9-4-97, 19...  
Date completed 9-5-97, 19...

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>12</u>		

9. WATER LEVEL  
Static water level 142 feet below land surface  
Artesian flow G.P.M. 12 P.S.I.  
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name WAYNE DRILLING, INC. Contractor  
Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510 Contractor  
Nevada contractor's license number 0022549 issued by the State Contractor's Board  
Nevada driller's license number 923 issued by the Division of Water Resources, the on-site driller  
Signed Wayne Drilling, Inc. driller performing actual drilling on site or contractor  
Date September 8, 1997