

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

**WELL DRILLER'S REPORT**  
 Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38319

1. OWNER LARRY TAYLOR ADDRESS AT WELL LOCATION Same  
 MAILING ADDRESS 8475 Holiday Lane  
Reno, Nevada 89511  
 2. LOCATION SW 1/4 SW 1/4 Sec 1 T. 18N N/S R 19 E Washoe County  
 PERMIT NO. R-310 040-631-03 SW Reno  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other.....  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Top soil		0	3	3
Boulders, gravel with sandy clay		3	9	6
Large dia boulders, gravel with sandy clay		9	17	8
Brown clay		17	20	3
Sandy gravel & boulders		20	31	11
Sandy clay		31	47	16
Brown clay, tight		47	49	2
Boulders & gravel		49	53	4
Clay mixed with small gravel (brown)		53	66	13
Sandy clay (brown)		66	69	3
Brown clay, tight		69	76	7
Brown sandy clay, soft		76	105	29
Brown sandy clay, tight		105	108	3
Brown sandy clay, soft		108	115	7
Sand & gravel	X	115	118	3
Brown clay, tight		118	125	7
Tanish brown clay, softer		125	140	15
Tanish brown clay, tight		140	147	7
Sandy clay/sand, softer		147	163	16
Tanish brown clay, tight		163	167	4
Sandy clay, very soft		167	173	6
Tanish clay, tight		173	180	7
Sand & small gravel		180	185	5
Clay, tight		185	189	4
Sand & small gravel	X	189	208	19
Sandy clay, med soft		208	209	1

8. WELL CONSTRUCTION  
 Depth Drilled 220 Feet Depth Cased 223 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 9 7/8 Inches To 0 Feet 220 Feet  
 Inches Feet Feet  
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	223

Perforations:  
 Type perforation factory sawed slot  
 Size perforation 3/32 x 3 x 5 around  
 From 160 feet to 220 feet  
 From feet to feet  
 From feet to feet  
 From feet to feet  
 From feet to feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout  
 Depth of Seal 100 feet  
 Placement Method:  Pumped  Poured  
 Gravel Packed:  Yes  No  
 From 100 feet to 220 feet

9. WATER LEVEL  
 Static water level 0 feet below land surface  
 Artesian flow over top G.P.M. 85+ P.S.I.  
 Water temperature cold °F Quality clear

Date started 7-22-98, 19  
 Date completed 7-25-97, 19

WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift			
Sand & gravel	85+	X	209 218 9
Plug driven in casing			
Med. hard formation			218 223 5

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510  
 Nevada contractor's license number issued by the State Contractor's Board 0022549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date July 28, 1997