

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37089

Ann Louis Cantlon Trust/  
 LAWRENCE J. WEISS Ph.D.

1. OWNER Ann Louis Cantlon Trust/LAWRENCE J. WEISS Ph.D. ADDRESS AT WELL LOCATION Lot W Willomonte Road  
 MAILING ADDRESS Sanford Center for Aging/146 Reno, Nevada 89557-0133 Reno, Nevada 89511

2. LOCATION SW 1/4 SE 1/4 Sec. 3 T. 17N N/S R. 20 E Washoe County  
 PERMIT NO. 050-520-31 Willomonte Ranch, Steamboat  
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Top soil with volcanic rock		0	1	1
Gray volcanic rock		1	24	23
Brown volcanic rock		24	38	14
Gray volcanic rock		38	65	27
Rusty soft volcanic rock		65	68	3
Brown volcanic rock		68	99	31
Purple volcanic rock		99	115	16
Brown volcanic rock		115	165	50
Rusty fracture rock		165	169	4
Brown volcanic rock		169	224	55
Fractured rock (app. 3 to 5 GPM)	X	224	226	2
Brown volcanic rock		226	236	10
Weathered fracture rock	X	236	268	32
Brown volcanic rock		268	275	7

8. WELL CONSTRUCTION  
 Depth Drilled 275 Feet Depth Cased 275 Feet

HOLE DIAMETER (BIT SIZE)  
 From 10 Inches To 50 Feet  
8 5/8 Inches 50 Feet 275 Feet  
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	275

Perforations:  
 Type perforation Factory sawed slot  
 Size perforation 3/32 x 3 x 5 around  
 From 230 feet to 270 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
 From 50 feet to 275 feet

9. WATER LEVEL  
 Static water level 216 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. 25 P.S.I.  
 Water temperature 68 °F Quality clear

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510  
 Nevada contractor's license number issued by the State Contractor's Board 0022549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date October 1, 1997

Date started 9-29-97, 19\_\_\_\_  
 Date completed 9-30-97, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:  Bailor  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>25</u>		