

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT No. 29686

1. OWNER Donald Iowa Mitchell ADDRESS AT WELL LOCATION \_\_\_\_\_  
MAILING ADDRESS PO Box 1266 \_\_\_\_\_  
Sparks, NV 89426 \_\_\_\_\_  
2. LOCATION SE 1/4 NE 1/4 Sec. 5 T. 17 S. R. 25 @ Upton County \_\_\_\_\_  
PERMIT NO. 17-103-24 Parcel No. \_\_\_\_\_  
Subdivision Name Steele Parcels

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND		0'	2'	2'
CLAY		2'	52'	50'
FINE SAND		52'	54'	2'
GRAY CLAY		54'	57'	3'
TUFF SAND		57'	102'	45'
BROWN CLAY		102'	105'	3'
SAND & GRAVEL	✓	105'	127'	22'

8. WELL CONSTRUCTION  
Depth Drilled 127 Feet Depth Cased 127 Feet

HOLE DIAMETER (BIT SIZE)  
From 0 Feet To 50 Feet  
12 Inches  
From 0 Feet To 127 Feet  
8 Inches

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>9 5/4</u>		<u>1 3/4</u>	<u>0</u>	<u>127</u>

Perforations:  
Type perforation MACHINED  
Size perforation 1/8 X 3  
From 115 feet to 125 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
Depth of Seal 50  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

9. WATER LEVEL  
Static water level 50 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. P.S.I.  
Water temperature Cold °F Quality Good

Date started Nov 1 1997  
Date completed Dec 24 1997

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input checked="" type="checkbox"/> Pump <input type="checkbox"/> Air Lift	<u>30</u>	<u>5'</u>	<u>4</u>

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name VERNON CANNON JR Contractor  
Address 4555 Hwy 50W Contractor  
Silver Springs NEV  
Nevada contractor's license number issued by the State Contractor's Board 23317  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1455  
Signed Vernon Cannon Jr.  
By driller performing actual drilling on site or contractor  
Date Dec 24 1997

RECEIVED  
NOV 2 10 10:00  
STATE ENGINEERING OFFICE