

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **70347**
 Rec. _____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Morning View Heights Driller Effinger Bros.
 Address Oakey Street at 17th Street Address 212 Anderson Lane Lic. No. 105
 Location of well: $\frac{1}{4}$ Sec. 02 21 061 T. N/6, R. 1 E, in Clark County
 or _____
 Water will be used for Refrigeration Total depth of well 40 feet
 Size of drilled hole 8 Inch Weight of casing per linear foot 9.4 lbs
 Thickness of casing 10 Guage Temp. of water _____
 Diameter and length of casing 6 5/8" OD 40 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 5' & 7 1/2' from top of casing
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well October 12, 1954 Date of completion of well October 13, 1954
 Type of well rig "71 Speed Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.	
Pump Well					
0	3	3	Limestone	Chief aquifer (water-bearing formation) from <u>14</u> to <u>16</u> ft. Other aquifers <u>9-12</u> First water at <u>9</u> feet. Casing perforated from <u>10</u> to <u>40</u> ft. Size of perforations <u>1/8" X 12"</u>	
3	5	2	Cement Gravel		
5	9	4	Yellow Clay		
9	12	3	Sand (Water)		
12	14	2	Limestone		
14	16	2	Gravel (Water)		
16	25	9	White Sand		
25	40	15	Red Sandy Clay		
Discharge Well					
0	3	3	Limestone		
3	5	2	Cement Gravel		
5	9	4	Yellow Clay		
9	12	3	Sand (Water)		
12	14	2	Limestone		
14	16	2	Gravel (Water)		
16	25	9	White Sand		
25	40	15	Red Sandy Clay		

