

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **70348**  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Morning View Heights Driller Effinger Bros.  
 Address Oakey Street at 17th Street Address 212 Anderson Lane Lic. No. 105  
 Location of well:  $\frac{1}{4}$  Sec. 02, T. 21 N. S. R. 16 E, in Clark County  
 or \_\_\_\_\_  
 Water will be used for Refrigeration Total depth of well 40 feet  
 Size of drilled hole 8 Inch Weight of casing per linear foot 9.4 lbs.  
 Thickness of casing 10 Guage Temp. of water \_\_\_\_\_  
 Diameter and length of casing 6 5/8" OD 40 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 7'6" & 7'6" from top of casing  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well October 13, 1954 Date of completion of well October 16, 1954  
 Type of well rig "71 Speed ?Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
<b>Pump Well</b>				
0	6	6	Yellow Clay	Chief aquifer (water-bearing formation) from <u>28</u> to <u>31</u> ft. Other aquifers <u>11@21</u>  First water at <u>11</u> feet.  Casing perforated from <u>10</u> to <u>40</u> ft.  Size of perforations <u>1/8" X 12"</u>
6	11	5	Cement Gravel	
11	21	10	Gravel (Water)	
21	28	7	Cement Gravel	
28	31	3	Gravel (Water)	
31	40	9	Red Sandy Clay	
<b>Discharge Well</b>				
0	6	6	Yellow Clay	
6	11	5	Cement Gravel	
11	21	10	Gravel (Water)	
21	28	7	Cement Gravel	
28	31	3	Gravel (Water)	
31	40	9	Red Sandy Clay	

