

OFFICE USE ONLY  
 Log No. 70797  
 Permit No. \_\_\_\_\_  
 Basin. 137B

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTEREST NO. 92815

1. OWNER ED & BELVA TOMANY ADDRESS AT WELL LOCATION 3 MILES NORTH FROM  
 MAILING ADDRESS PO BOX 452 ENO. OF PENOLA LANE.  
TONOPAH NEV 89049 Round Mountain, NV

2. LOCATION SE 1/4 SW 1/4 Sec. 9 T. 11N N/S R. 43 E NYE County  
 PERMIT NO. 10-211-12 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
SAND		100	108	8
BRN CLY		108	111	3
SMALL GRAVEL		111	114	3
BRN CLY		114	118	4
GRAVEL	X	118	129	11
CLY & SAND STRIMBERS		129	140	11
COARSE SAND		140	150	10
BRN CLY		150	158	8
SMALL GRAVEL		158	165	7
BRN CLY		165	171	6
GRAVEL	X	171	190	19
TAN CLY		190	195	5

8. WELL CONSTRUCTION  
 Depth Drilled 195 Feet Depth Cased 195 Feet

HOLE DIAMETER (BIT SIZE)  
 From To  
6 1/8 Inches 100 Feet 195 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>5 9/16</u>	<u>10.2</u>	<u>1.88</u>	<u>100</u>	<u>195</u>

Perforations:  
 Type perforation MILLED SLOT  
 Size perforation 3/8  
 From 120 feet to 130 feet  
 From 170 feet to 190 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

9. WATER LEVEL  
 Static water level Flowing feet below land surface  
 Artesian flow 12 G.P.M. 40 ~~FE~~  
 Water temperature 58 °F Quality Good

Date started 5-27, 1997  
 Date completed 5-28, 1997

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>40</u>	<u>0</u>	<u>5 hrs</u>

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WOYTEK DRILLING CO. INC. Contractor  
 Address 2220 STONE DR. Contractor  
RENO NEV 89511

Nevada contractor's license number issued by the State Contractor's Board: 024521A  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 1442

Signed Thomas M. Harris  
 By driller performing actual drilling on site or contractor  
 Date 5-28 97