WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 71456
Permit No.
Basin 51

NOTICE OF INTENT NO.

1. OWNER Newmont Gold Co.
MAILING ADDRESS PO Box 669
Carlin, NV 89822-0669

ADDRESS AT WELL LOCATION Gold Quarry
Newmont - 7 mi. Nth of Carlin

2. LOCATION SE ¼ SE ¼ Sec. 2 T. 33 N/S R. 51 E. Eureka County
PERMIT NO. M/O - 60871 T (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic MINING ☐ Irrigation ☐ Test
☑ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Placed materials for abandonment from — | | 1650 | 50 | 1600 |
| Well was gravel packed — | | 1660 | 525 | 1135 |
| 32" csng was cemented — | | 938 | 0 | 938 |
| No debris encountered on abandonment. | | | | |
| Materials used - 830 SKS 3/4 hole plug | | | | |
| 160 SKS Aqua-Gel | | | | |
| 805 SKS Casing Seal | | | | |
| 192 SKS Quick Gel | | | | |
| 5-3000# SKS #8 casing Seal | | | | |
| 72,500 Gals $H_2O$ | | | | |

Date started 11-14, 19 97
Date completed 11-17, 19 97

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 1670 Feet Depth Cased 1650 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| Inches | Feet | Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 40" | Surface Csng | | 0 | 40 |
| 32" | intermediate | | 0 | 938' |
| 24" | | | 525 | 970' |

Perforations:
Type perforation Roscoe Moss Louver "full flow" 24"
Size perforation
From 970 feet to 1650 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 ft.
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 525 feet to 1670' feet

9. WATER LEVEL
Static water level 500' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Sheridan McClard (Contractor)
Address Hc-30 Box 102 Elko, NV 89801 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0026661
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1631
Signed Sheridan McClard (By driller performing actual drilling on site or contractor)
Date 12-8-97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627