WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 111371
Permit No.
Basin 153
NOTICE OF INTENT NO. 32374

1. OWNER JOHN ADAMS & KEN CONLEY
MAILING ADDRESS EUREKA NEV. 89316
ADDRESS AT WELL LOCATION [illegible]

2. LOCATION NE ¼ SE ¼ Sec. 34 T. 21 N/S R. 53 E. EUREKA County
PERMIT NO. 19492 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☐ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP SOIL		TOP	8	8
CLAY		8	24	16
SAND. GRAVEL		24	31	7
CLAY		31	45	14
FINE SAND.		45	50	5
CLAY		50	63	13
SAND GRAVEL		63	74	11
CLAY		74	82	8
Sand GRAVEL		82	90	8
CLAY		90	99	7
SAND GRAVEL	33	99	132	33
CLAY		132	141	9
SAND GRAVEL	3	141	144	3
CLAY		144	145	1
SAND GRAVEL	39	145	184	39
CLAY		184	188	4
SAND GRAVEL	3	188	191	3
CLAY		194	199	5
SAND GRAVEL	5	199	204	5
CLAY		204	210	6
SAND GRAVEL	10	210	220	10
CLAY (WHITE Sand		220	236	16
SOME GRAVEL)				
	Replacement for Well Log			
	6675 which Was Plugged			
	by Well Log # 111525			

Date started 5-12, 1998
Date completed 5-14, 1998

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	Replaces Well Log 6675	
	which was plugged by	
	NOI 64972	

8. WELL CONSTRUCTION
Depth Drilled 236 Feet Depth Cased 236 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
27 Inches	TOP Feet	236 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16"		¼	TOP	236

Perforations:
Type perforation ROSCOE MOSS
Size perforation ⅛"
From 126 feet to 236 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From TOP feet to 236 feet

9. WATER LEVEL
Static water level 116 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WALTER R. DLASKETT (Contractor)
Address BOX 10 (Contractor)
EUREKA NEV 89316
Nevada contractor's license number issued by the State Contractor's Board 11882
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 635
Signed James E. Groth (By driller performing actual drilling on site or contractor)
Date 5-30-98

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627