WELL "O"

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 72635
Permit No.
Basin 212

NOTICE OF INTENT NO. 16583

1. OWNER American Pacific Corp.
MAILING ADDRESS 3770 Howard Hughes Pkwy #306 LV NV 89107
ADDRESS AT WELL LOCATION Street Right of way

2. LOCATION NE ¼ NE ¼ Sec. 2 T. 22 N/S R. 62 E County
PERMIT NO. (Issued by Water Resources) 161-35-899-004 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ASPHALT & road bed		0	2'	
H grey gravel w/silt				
sand w silt & gravel		2'	14'	
dk brn cem sand & gravel		14'	16'	2'
sand		16'	20.5'	
dk brn cem stg		21'	22'	1'
dk brn gravel & sand fine med gravel		22	23.5	1.5'
cemented stg		23.5	27'	
water ▽ encon		27'		
dk brn cem stg w/		30'	33'	
sandy lean clay w/gravel stg		33'	35'	
dk brn cem stg		35'	38.5'	
red brn sandy lean clay, wet		38.5	40	

Date started Dec 22, 19 97
Date completed, 19

7. WELL TEST DATA
TEST METHOD: ☑ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA	Total	

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	40 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		SCH 40	0	40

Perforations:
Type perforation machine slotted
Size perforation .020
From 20 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 18'
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 18 feet to ~~surface~~ 40 feet

9. WATER LEVEL
Static water level 27.0 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name G.E.S (Contractor)
Address 7560 W. Sahara (Contractor)

Nevada contractor's license number issued by the State Contractor's Board: Engineer
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2044
Signed (By driller performing actual drilling on site or contractor)
Date 2-17-98

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627