

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 32591

1. CONSULTANT SUMMIT ENGINEERS & SURVEYORS ADDRESS AT WELL LOCATION _____
 1. OWNER _____ MAILING ADDRESS 5405 Mae Anne Avenue 2200 I-80 West/P.O. Box 399
Reno, Nevada 89523 Verdi, Nevada 89439
 2. LOCATION NW 1/4 NW 1/4 Sec 16 T. 19N N/S R 18 E Washoe County
 PERMIT NO. MW-2A 038-100-27 Boomtown, Verdi
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED New Well Replace Recondition Deepen Abandon Other _____
 4. PROPOSED USE Domestic Municipal/Industrial Irrigation Monitor Test Stock Air Rotary RVC Other TUBEX _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Tan to brown, fine to med dense, mostly sand, some silt	med. silty sand, dry,	0	1/2	1/2
Gray med to coarse, silty sandy gravel, dense to very dense, mostly gravel, some sand, some silt, minor boulders		1/2	5	4 1/2
Gray to brown, coarse, sandy gravel, med dense some coarse gravel		5	10	5
Tan, med to coarse, graveley silty sand, med. dense, mostly sand, some gravel, some silt		10	16	6
gray to brown, coarse sandy gravel, med dense mostly gravel, some sand minor silt		16	24	8
Tan to gray, coarse, silty sandy gravel, med dense, mostly gravel, some sand, some cemented silt, minor clay		24	33	9
Black to tan, coarse sandy gravel, dense, mostly coarse gravel, some coarse sand, minor to some boulders		33	47	14
Brown to tan, coarse, clayey sandy gravel, med dense, mostly coarse gravel, some sand, some clay		47	53	6
Brown, med. clayey sand, med dense, some sand some clay, minor gravel		53	60	7
Brown, coarse clayey gravel, med dense to dense some gravel, clay & sand		60	71	11
Brown, med. clayey sand, med. dense, some sand				

8. WELL CONSTRUCTION
 Depth Drilled 95.6 Feet Depth Cased 95 Feet
 HOLE DIAMETER (BIT SIZE)
 From 8 5/8 Inches To 0 Feet 95.6 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC	sch 40		0	95
4" box cap, water proof locking cap				
Steel monument				

Perforations:
 Type perforation factory sawed slot
 Size perforation 0.020"
 From 45 feet to 95 feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type: Neat Cement Cement Grout Concrete Grout
 Depth of Seal 41 feet
 Placement Method: Pumped Poured
 Bentonite Seal: 41 to 43 ft.
 Gravel Packed: Yes No #8 SRI Sand
 From 43 feet to 95.6 feet

9. WATER LEVEL
 Static water level 67.4 feet below land surface
 Artesian flow _____ G.P.M. not known p.s.i.
 Water temperature k/n °F Quality not known

Date started 8-3-98, 19____
 Date completed 8-12-98, 19____

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
<u>some clay, minor gravel</u>		<u>71</u>	<u>81</u>
<u>Increase gravel with depth</u>			
<u>Brown to gray, coarse sandy gravel, med dense mostly gravel, some sand</u>			
<u>minor clay</u>		<u>81</u>	<u>96</u>

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number 0022549 issued by the State Contractor's Board
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923/908
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date August 31, 1998