H-9 Abandonment

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 73203
Permit No.
Basin 54

NOTICE OF INTENT NO. 39144

1. OWNER Cortez Gold Mine
MAILING ADDRESS HC66-50
Beowawe, NV 89821

ADDRESS AT WELL LOCATION
cortez Gold MIne

2. LOCATION SE ¼ NE ¼ Sec. 21 T. 28N N/S R. 47 E. Lander County
PERMIT NO. M/O-1003 (Issued by Water Resources) n/a (Parcel No.) n/a (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Pumped neat cement from 100' to surface using 16.30 gallons cement				

Date started 4-25, 1998
Date completed 4-25, 1998

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 100 Feet Depth Cased 95 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 1/4 Inches	0 Feet	100 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
.312	.69	SCH40	+2	90

Perforations:
Type perforation slot
Size perforation .020
From 90 feet to 98 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 32
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout Xhole plug

Gravel Packed: ☒ Yes ☐ No
From 82 feet to 100 feet

9. WATER LEVEL
Static water level 63 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address PO Box 5279 (Contractor)
Elko, NV 89802

Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2000

Signed Bill Eddy (By driller performing actual drilling on site or contractor)
Date 4-25-98

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

H-9

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No.
Permit No.
Basin

NOTICE OF INTENT NO. 33467

OWNER: CORTEZ GOLD MINES
MAILING ADDRESS: HC 56-50
BEOWAWE, NV 89821

ADDRESS AT WELL LOCATION: CORTEZ GOLD MINE SITE

2. LOCATION: SW ¼ NE ¼ Sec. 21 T. 28 N/S R. 47 E LANDER County

PERMIT NO. M/C-1002 (Issued by Water Resources) | Parcel No. N/A | Subdivision Name N/A

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
[illegible]		0	100	100

Date started: DECEMBER 16, 19[illegible]
Date completed: DECEMBER 17, 19[illegible]

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled: 100 Feet Depth Cased: [illegible] Feet

HOLE DIAMETER (BIT SIZE)

		From	To
[illegible] Inches		0 Feet	100 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation: SLOT
Size perforation: .020
From 30 feet to 100 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal: 32
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout ☒ BOTTOM PLUG
Gravel Packed: ☒ Yes ☐ No
From 32 feet to 100 feet

9. WATER LEVEL
Static water level: 32 feet below land surface
Artesian flow: G.P.M. P.S.I.
Water temperature: COLD °F Quality: GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name: [illegible] (Contractor)
Address: P.O. BOX [illegible] (Contractor)
[illegible], NV 89803

Nevada contractor's license number issued by the State Contractor's Board: [illegible]
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: [illegible]

Signed: (By driller performing actual drilling on site or contractor)
Date:

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627