





HOLE ABANDONMENT REPORT

HOLE NUMBER:

MW-1 6" casing

COORDINATES: COORDINATES

north east

LOCATION: 1/4 Section Township: Range:

NW 1/4 SW 1/4 2 42.N 53E

DATE DRILLED: CONTRACTOR/RIG #: HOLE DEPTH:

? Rimrock 375' feet

STATIC WATER LEVEL: FLOWING WELL

feet (check box)

AQUIFERS ENCOUNTERED: AQUIFERS ENCOUNTERED: NONE (check box):

feet feet

DATE PLUGGED PLUGGED BY (company & rig) SURFACE SEAL CEMENT? CONCRETE?

8-4-98 Summit Drilling Fluids feet

Recommended Amt. Percent

Material Used (check box)

Amount Used Cost/Unit Cost

Coarse bentonite

Concrete/cement

9 Bags Gel 50 LBS.

9 Bags Barite 100 LBS.

Bentonite slurry

weight:

viscosity:

TOTAL COST

COST/FT

Nevada state regulations require:

- 1. All holes must be plugged.
2. Surface seal of neat concrete must extend to a minimum depth of 10 feet.
3. IMC policy forbids backfilling holes with cuttings.
4. If plugged with bentonite slurry, slurry must weigh at least 9 pounds per gallon and have a viscosity of at least 50 seconds. Barite should be used to increase the weight. More bentonite or mixing longer will increase viscosity. Soda ash added to the water first will expedite viscosity yield.
5. If plugged with chipped, coarse bentonite, introduction below the water level may not exceed 50 pounds per two minutes.

REMARKS (j.e., hole left open for survey, geologic reasons):

ran Pull Pipe down to 340' for trimy line - raised over 13% solids
pumped down pipe & displac H2O. Cement Top 20'

Signature: Ward Weaver (certifies statements to be true)

1125 Gals.

2 mixed over 13% solids & pumped down trimy line
6 Bags Cement 94 LBS. Top 20'