



HOLE ABANDONMENT REPORT

HOLE NUMBER:

MW-4

COORDINATES:

COORDINATES

north east

LOCATION: ¼ Section

Township:

Range:

NW¼ SW¼ 2 42N 53E

DATE DRILLED:

CONTRACTOR/RIG #:

HOLE DEPTH:

Rimrock-3477 300' feet

STATIC WATER LEVEL:

FLOWING WELL

(check box)

103½' feet

AQUIFERS ENCOUNTERED:

AQUIFERS ENCOUNTERED:

NONE

(check box):

feet feet

DATE PLUGGED

PLUGGED BY
(company & rig)

SURFACE SEAL

CEMENT? CONCRETE?

8-3-98 Summit Drilling Fluids 15 feet No

Recommended Amt. _____ Percent _____

Material Used

(check box)

Amount Used

Cost/Unit

Cost

Coarse bentonite

Concrete/cement

5 Bags Geh- 50 LBS.

5 Bags Barite-100 LBS.

Bentonite slurry

weight: _____

viscosity: _____

Nevada state regulations require:

1. All holes must be plugged.
2. Surface seal of neat concrete must extend to a minimum depth of 10 feet.
3. IMC policy forbids backfilling holes with cuttings.
4. If plugged with bentonite slurry, slurry must weigh at least 9 pounds per gallon and have a viscosity of at least 50 seconds. Barite should be used to increase the weight. More bentonite or mixing longer will increase viscosity. Soda ash added to the water first will expedite viscosity yield.
5. If plugged with chipped, coarse bentonite, introduction below the water level may not exceed 50 pounds per two minutes.

REMARKS (i.e., hole left open for survey, geologic reasons):

Run 280 of Drill pipe for trimline - mixed 13% plus mud & pumped down
Line to Replace H2O. Cement Top 15'

Signature: Ward Weaver

(certifies statements to be true)

3als.
625

mixed over 13% solids & pumped down Drill pipe.
2 Bags Cement 94 LBS.
Top 15'

TOTAL COST _____

COST/FT _____

pumped down