WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 74082
Permit No.
Basin 212

NOTICE OF INTENT NO. 18609

1. OWNER Ted Wiens Tire & Auto Centers
MAILING ADDRESS 1710 las Vegas Blvd. South las Vegas, Nevada 89104
ADDRESS AT WELL LOCATION 4845 South Pecos Road Las Vegas, Nevada

2. LOCATION SE ¼ SE ¼ Sec. 24 T. 21 N/S R. 61 E. Clark County
PERMIT NO. (Issued by Water Resources) 162-24-802-010 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED: ☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE: ☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE: ☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown silty sand w/ caliche & gravel no plasticity/low moisture, sub-angular gravel & caliche		0	5	
Reddish brown silty clay w/ caliche, low to mod plasticity/low moisture		5	8	
Reddish brown silt w/ caliche no plasticity/low moisture		8	12	
Brown silt w/ gravel no plasticity/low moisture		12	15	
Caliche		15	16	
Brown clayey silt w/ gravel sub-rounded gravel, mod plasticity/low moisture		16	20	
Brown clayey silt w/ sub-rounded gravel, mod-plasticity/low moisture		20	25	
Brown silt w/ gravel & caliche sub-rounded gravel & caliche, low plasticity/low moisture		25	30	
Brown clayey silt/gravel & caliche, sub-rounded gravel & caliche low to mod plasticity/low moisture		30	35	
Brown silty clay		35	40	
Brown clay w/ silt		40	45	

Date started 2.9, 1999
Date completed 2.9, 1999

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

RECEIVED FEB 8 1999 LAS VEGAS OFFICE

8. WELL CONSTRUCTION
Depth Drilled 45 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 Inches	0 Feet	45 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2			0	25

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 25 feet to 45 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 22
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 22 feet to 45 feet

9. WATER LEVEL
Static water level 35 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, Inc. (Contractor)
Address 301 W. Deer Valley Rd #7 Phoenix Arizona 85027 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M3070
Signed John Manley
By driller performing actual drilling on site or contractor
Date 3/2/99

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627