WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 74116
Permit No.
Basin 212

NOTICE OF INTENT NO. 18615

1. OWNER Southland Corporation
MAILING ADDRESS 10220 SW Greenburg Rd #170 Portland, Oregon 97223
ADDRESS AT WELL LOCATION 600 North Las Vegas Blvd Las Vegas, Nevada Clark County

2. LOCATION SE ¼ SE ¼ Sec. 27 T. 20 N/S R. 61 E/W
PERMIT NO. (Issued by Water Resources) 139-27-205-002 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED: ☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE: ☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE: ☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand Fine To Medium grained, light brown slightly moist, dense, No HCO/HCS		0	3	
Color change To pale yellow clayey Sand Increasing gravels, Dense, No HCO/HCS		3	5	
Caliche, Highly Fractured, Fine To medium grained pale yellow - Dry very dense No HCO/HCS		5	9	
Caliche, highly cemented pale yellow.		9	30	
Sandy gravel, medium To Coarse grained pale gray, very dense wet, strong HCO, Some HCS		30	30	

TOTAL DEPTH 60 feet

Date started 2-1, 19 99
Date completed 2-1, 19 99

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
8	0	30

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"			0	10

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 10 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 9
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 9 feet to 30 feet

9. WATER LEVEL
Static water level 8 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, Inc. (Contractor)
Address 201 W. Deer Valley Road #7 Phoenix, Arizona 85027 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller U2079
Signed (Driller performing actual drilling on site or contractor)
Date 2/24/99

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627