

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 74818  
 Permit No. \_\_\_\_\_  
 Basin 105  
 NOTICE OF INTENT NO. 40323

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER **Ed Kawchack**  
 MAILING ADDRESS **3239 E Lake Blvd**  
**Washoe Valley, NV 89704**

ADDRESS AT WELL LOCATION **604 Stagecoach Rd**  
**Gardnerville, Nv 89410**

2. LOCATION **SE 1/4 SE 1/4 Sec. 24 T 12** N/S R **20 E** **Douglas** County  
 PERMIT NO. 1220-25-510-006 ~~29-431-21~~ **Thompson Acres Lot 21 Block A**  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other  **mud**

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Brown D.G. with boulders		0	15	
Multi colored large gravels with boulders		15	25	10
Multi colored course sand & gravels with brown clay balls		25	40	15
Multi colored course sand & gravels		40	55	15
Multi colored gravels with brown clay balls		55	65	10
Multi colored gravels with course sand		65	125	60
Multi colored course sand		125	160	35
Multi colored gravels with brown clay balls		160	200	40
Multi colored gravels & course sand		200	235	35
Multi colored gravels with fine sand		235	240	5
Multi colored volcanic rock with brown sandy clay balls		240	300	60
Multi colored course sand with brown clay		300	320	20

8. WELL CONSTRUCTION  
 Depth Drilled **320** Feet Depth Cased **320** Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0	100
8 1/2 Inches	100	320

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	17.0	.225	+ 1 1/2	320

Perforations:  
 Type perforation **factory sawed**  
 Size perforation **3X32X3**

From	feet to	feet
300	320	feet
	feet to	feet
	feet to	feet
	feet to	feet

Surface Seal:  Yes  No  
 Depth of Seal **50'**  
 Placement Method:  Pumped  Poured  
 Seal Type:  Neat Cement  Cement Grout  Concrete Grout

Gravel Packed:  Yes  No  
 From **320** feet to **50** feet

9. WATER LEVEL  
 Static water level **200** feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature **cool** °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name **A.S.A.P. Pump & Well Service, Inc.** Contractor  
 Address **P.O. Box 60130** Contractor  
**Reno, Nv 89506**  
 Nevada contractor's license number issued by the State Contractor's Board **35387-A**  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller **2066**  
 Signed *Tony Welch*  
 By driller performing actual drilling on-site or contractor  
 Date **1/26/99**

Date started **1/20/99**, 19\_\_\_\_  
 Date completed **1/25/99**, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	TEST METHOD:	
	G.P.M.	Time (Hours)
<input type="checkbox"/> Bailor <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<b>20+</b>	<b>2 hours</b>
Draw Down (Feet Below Static)		

RECEIVED  
 1/28 AM 9:56  
 STATE ENGINEERING OFFICE