


*Duzl Completion*



PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 40413

1. OWNER BARRICK GOLDSTRIKE MINES ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE  
MAILING ADDRESS P.O. BOX 29 MINE SITE  
ELKO, NV 89803

2. LOCATION NW 1/4 NW 1/4 Sec. 30 T. 36 N S R. 50 E EUREKA County  
PERMIT NO. N/A Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  Domestic  Irrigation  Test  Cable  Rotary  RVC  
 Deepen  Abandon  Other  Municipal/Industrial  Monitor  Stock  Air  Other

6. LITHOLOGIC LOG				
Material	Water Strata	From	To	Thick-ness
DUMP MATERIAL		0	15	15
CLAYSTONE		15	85	70
CLAYSTONE WITH BLACK ROCK		85	100	15
BLACK ROCK WITH GRAVEL		100	120	20
TAN CLAY		120	140	20
TAN CLAY WITH GRAVEL		140	150	10
BLACK ROCK WITH GRAVEL		150	185	35
GRAY CLAY		185	200	15
BLACK ROCK WITH CLAY		200	210	10
BLACK ROCK WITH GRAVEL		210	245	35
GRAY ROCK WITH CLAY		245	260	15
TAN CLAY		260	270	10
GRANITE WITH CLAY		270	275	5
GRANITE		275	300	25
BROWN CLAY		300	350	50
LIMESTONE WITH BROWN CLAY		350	355	5
GRAY AND BLACK ROCK WITH CLAY		355	410	55
BROWN ROCK		410	430	20
BLACK ROCK		430	450	20
BLACK ROCK WITH CLAY		450	460	10

8. WELL CONSTRUCTION  
Depth Drilled 720 Feet Depth Cased \_\_\_\_\_ Feet  
HOLE DIAMETER (BIT SIZE)  
From \_\_\_\_\_ To \_\_\_\_\_  
1.7 1/2 Inches \_\_\_\_\_ Feet \_\_\_\_\_ 8.0 Feet  
7 7/8 Inches \_\_\_\_\_ 8.0 Feet \_\_\_\_\_ 7.20 Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.75	40.48	0.365	+2	80
1:1.66	2.27	SCH. 80	+2	570
2:2.375	3.65	0.154	+2	700

Perforations:  
Type perforation SLOTTED  
Size perforation  
From 1: 550 feet to 570 feet  
From 2: 680 feet to 700 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
Depth of Seal 80' SURFACE  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
Gravel Packed:  Yes  No 1: 540' - 580'  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet 2: 670' - 720'

9. WATER LEVEL  
1: 347.1 Static water level 2: 349.5 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started SEPTEMBER 14, 19 98  
Date completed SEPTEMBER 19, 19 98

7. WELL TEST DATA			
TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name LANG EXPLORATORY DRILLING Contractor  
Address P.O. BOX 5279 Contractor  
ELKO, NV 89802  
Nevada contractor's license number issued by the State Contractor's Board 0021976  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1796  
Signed RON BEHREANDT  
By driller performing actual drilling on site or contractor  
Date SEPTEMBER 19, 1998

*B.S.L.*

