

WHITE-DIVISION OF WATER RESOURCES
CANARY-CLIENT'S COPY
PINK-WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. 74844
Permit No. _____
Basin. 61

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

NOTICE OF INTENT NO. 39242

1. OWNER BARRICK GOLDSTRIKE MINES ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE
MAILING ADDRESS P.O. BOX 29 MINESITE NORTH OF CARLIN, NV
ELKO, NV 89803

2. LOCATION SW 1/4 SE 1/4 Sec. 19 T. 36 N/S R. 50 E EUREKA County
PERMIT NO. N/A Issued by Water Resources Parcel No. N/A
Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other
4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
GRAY & WHITE ROCK		0	180	180
BLACK ROCK		180	240	60
GRAY & WHITE ROCK		240	280	40
GREEN & GRAY FRAC-TURED ROCK		280	300	20
GREEN & GRAY ROCK		300	340	40
LOST CIRCULATION		340	420	80

8. WELL CONSTRUCTION
Depth Drilled 420 Feet Depth Cased 410 Feet
HOLE DIAMETER (BIT SIZE)
From To
1.4.75 Inches 0 Feet 35 Feet
8 Inches 35 Feet 420 Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.750	34.24	0.250	+1	35
1:1.66	2.27	0.140	+1	410
2:1.66	2.27	0.140	+1	275
3:1.66	2.27	0.140	+1	196

Perforations:
Type perforation DRILLED HOLES
Size perforation 0.187
From 1: 405 feet to 410 feet
From 2: 270 feet to 275 feet
From 3: 191 feet to 196 feet

CONSTRUCTION DETAILS

Material	From	To	Thick-ness
CEMENT	0	50	50
HOLE PLUG	50	185	135
GRAVEL PACK	185	200	15
HOLE PLUG	200	265	65
GRAVEL PACK	265	280	15
HOLE PLUG	280	400	120
GRAVEL PACK	400	420	20

Surface Seal: Yes No Seal Type:
Depth of Seal 50' Neat Cement
Placement Method: Pumped Cement Grout
 Concrete Grout
CONSTRUCTION DETAILS GIVEN IN LITH. LOG SECTION
Gravel Packed: Yes No
From feet to feet

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

9. WATER LEVEL
Static water level DRY feet below land surface
Artesian flow N/A G.P.M. 0 P.S.I.
Water temperature °F Quality

Date started FEBRUARY 25, 19 99
Date completed FEBRUARY 28, 19 99

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

Name LANG EXPLORATORY DRILLING Contractor
Address P.O. BOX 5279 Contractor
ELKO, NV 89802
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1948
Signed Waryl Hartzman
By driller performing actual drilling on site or contractor
Date FEBRUARY 25, 1999

B.S.T.L