WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 75387
Permit No.
Basin 212

NOTICE OF INTENT NO. 18602

1. OWNER Timer Fueling Facility
MAILING ADDRESS 8100 Lake Mead drive Henderson, nevada
ADDRESS AT WELL LOCATION 8100 Lake mead drive Henderson, nevada

2. LOCATION NE ¼ NW ¼ Sec. 12 T 22 X/S R 62 E Clark County
PERMIT NO. Issued by Water Resources | 178-13-100+004 Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand, light brown, medium gravel, loose, non plastic, slightly moist poorly sorted angular to subangular		5	10	
Sand as previously described w/ more gravel		10	15	
Sand as previously described more dense, minor caliche		15	20	
Sand, light brown, moderately well sorted, slightly plastic, loose		20	25	
Sand, brown, gravelly, poorly sorted non-plastic, dry moderately hard		25	30	
Sand as previously described slightly moist		30	35	
Sand as previously prescribed light reddish brown, hard, gypsum, sl. moist		35	40	
Fine sand, brown, moderately well sorted, slightly plastic, slightly moist, gravels		40	45	
silt, brown, well sorted, slightly plastic, loose, moist, minor gypsum		45	50	
Clayey silt, brown, well-graded, well sorted, moderately plastic, moist, dense,		50	55	
Clayey silt as described previously, very moist		55	60	
Clayey silt as previously described, very moist to wet		60	65	
silty clay, brown, plastic wet		65	68	
Clay, brown, plastic, v. moist		68	70	

Date started 3-23, 1999
Date completed 3-23, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 69 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12 Inches	0 Feet	69 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4			0	40

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 40 feet to 69 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 38
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 38 feet to 69 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, Inc. Contractor
Address 301 W. Deer Valley Rd #7 Contractor
Phoenix, Arizona 85027
Nevada contractor's license number issued by the State Contractor's Board 44809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M2070T1
Signed By driller performing actual drilling on site or contractor
Date 4/27/99

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627