WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 75390
Permit No.
Basin 212

NOTICE OF INTENT NO. 18602

1. OWNER Timet Freling Facility
MAILING ADDRESS 8100 Lake Mead Drive Henderson, NV
ADDRESS AT WELL LOCATION 8100 Lake Mead drive Henderson, Nevada

2. LOCATION NE ¼ NW ¼ Sec. 12 T. 22 X/S R. 62 E. Clark County
PERMIT NO. Issued by Water Resources | Parcel No. 178-13-101-004 | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
gravelly silt, brownish gray, poorly sorted gravel		0	5	
gravelly silt, brownish gray		8	10	
gravelly sand, brownish gray very poorly sorted gravel		14	16	
gravelly sand, gravel sand		19	21	
gravelly - same as above		24	26	
gravelly sand - silt, brown, non-plastic, poorly sorted		29	31	
gravelly silt, gravel sand brown non-plastic, dry, gravel sand		35	37	
fine sand to silty sand, brown, poorly sorted		40	42	
fine sand to silty sand		45	47	
sand w/minor gravel, brown loose				
fine sand, brown, trace gravel		50	52	
silty clay to clayey silt		53	57	
silt clay, brown, plastic		60	62	
clayey silt, brown silt		62	64	
silty clay brown, moderately plastic moist		65	67	

Date started 3.24, 1999
Date completed 3.25, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 67 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12 Inches	0 Feet	67 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4			0	40

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 40 feet to 67 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 38
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 38 feet to 67 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Company, Inc. (Contractor)
Address 301 W. Deer Valley Road, #7 Phoenix, Arizona 85027 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M3070
Signed (By driller performing actual drilling on site or contractor)
Date 4.25.99

RECEIVED MAY 24 1999 DIVISION OF WATER RESOURCES

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627