WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 75739
Permit No.
Basin 65

NOTICE OF INTENT NO. 71

1. OWNER Newmont Gold C.
MAILING ADDRESS Ft. [illegible]
Golconda NV

ADDRESS AT WELL LOCATION Lit[illegible]
16 mi West of Battle Mtn.

2. LOCATION NW ¼ SE ¼ Sec. 15 T. 34 N/S R. 42 E. Humboldt County

PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal Industrial ☐ Monitor ☐ Stock
Mining

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium & gravel		0	150	
Ben Hawkins Sh/Shale		150	340	9

RECEIVED
99 JUN -2 PM 1:05
STATE ENGINEER'S OFFICE

Date started 3-10, 19 99
Date completed 3-18, 19 99

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
150	7	6

8. WELL CONSTRUCTION
Depth Drilled 340 Feet Depth Cased 337 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
14 ¼ Inches	0 Feet	14 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 ⅝	19	¼	0	337
1¼	2	⅛	0	337
1¼	2	⅛	0	334

Perforations:
Type perforation Louvered
Size perforation
From 177 feet to 337 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 0 feet to 340 feet

9. WATER LEVEL
Static water level 150 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name AAA Drilling & Equipment Rental (Contractor)
Address PO Box 2487 Elko (Contractor)
NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0020634
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1670
Signed [illegible] (By driller performing actual drilling on site or contractor)
Date 3-24-99

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627

WELL # mdw-1

DRILLER Rob Oeschger

DATE OF COMPLETION 3-18-99

GEOLOGIST

SURFACE CASING

DIAMETER 16 INCHES

LENGTH 20 FEET

DEPTH FT

50 — Washed Pea Gravel to 50'

STATIC WATER LEVEL = 180 FT.

Screens start 160' to 337

2- 1 1/4 INCH SCH 80 ~~PVC~~ RISER steel

Sounder Tubes

____ INCH SCH 80 PVC SCREEN

8 5/8 To 337

340' T.D.

50 FT. CEMENT SURFACE SEAL 48 BAGS

HOLE DIAMETER 14 3/4 INCHES

VOLCLAY SEAL ____ BAGS

AND/OR

TYPE: ____

____ BENTONITE

____ BAGS

____ SAND SIZE

____ # BAGS

COMMENTS: Well produced 150 GPM.

RECEIVED
99 JUN -2 PM 1:05
STATE ENGINEERS OFFICE