

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

*11/9/99  
 ABANDON  
 HCM#5*

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37942

1. OWNER ROUND MTN GOLD CORP. ADDRESS AT WELL LOCATION 7 MILES EAST ON HWY 397 AT MANHATTAN MINE SITE  
 MAILING ADDRESS PO BOX 480 ROUND MTN NEVADA 89045  
 2. LOCATION SE 1/4 SE 1/4 Sec. 19 T. 8N N/S R. 44 E. NYE County \_\_\_\_\_  
 PERMIT NO. 35884 Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Municipal/Industrial  Irrigation  Test  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
MOVED IN R/L UP OVER WELL				
PULL 650' OF 4" COLUMN				
PIPE - PUMP MOTOR - PVC				
PIPE & ELECT CABLE OUT OF WELL & LAY DOWN				
PICK UP 700' OF 4" DRILL PIPE AND R/LH.				
NO OTHER DEBRIS FOUND IN WELL. WELL WAS NOT PERFORATED FROM 50' ABOVE SWL TO PERFS IN WELL AT 170' DUE TO CONDITION OF CASING - VERBAL WAIVER WAS GIVEN BY TELEPHONE FROM JASON KING AND TIM WILSON WITH THE OWR ON THIS PROCEDURE. (5-12-99) WELL WAS THEN CEMENTED FROM BOTTOM TO TOP - 29,200 LBS OF CEMENT WITH 1920 GALS OF WATER. DRILL WAS REMOVED CEMENTING IN 200' STAGES. THIS AMOUNT OF CEMENT WAS 50% ACCESS OF WELL VOLUME - R/LH NEXT DAY TALKED CEMENT AT 70' TOP JOB WAS THEN DONE ON WELL BRING CEMENT TO TOP OF WELL.				
TOTAL AMOUNT OF CEMENT USED 320 SCKS WATER 1920 GALS.				

8. WELL CONSTRUCTION  
 Depth Drilled 710 Feet Depth Cased 710 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 12 1/4 Inches To 0 Feet 710 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>8 5/8</u>	<u>22.36</u>	<u>1.250</u>	<u>+1</u>	<u>710</u>

Perforations:  
 Type perforation MILLED  
 Size perforation 3 X 1/8  
 From 170 feet to 300 16 SLOTS P.I.F. feet  
 From 300 feet to 710 32 SLOTS P.I.F. feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 50 feet to 710 feet

9. WATER LEVEL  
 Static water level 145' feet below land surface  
 Artesian flow NO G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature COLD °F Quality FAIR

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WOYTEK DRILLING CO. INC. Contractor  
 Address 2220 S. TOWIE DR. RENO NEVADA 89511 Contractor  
 Nevada contractor's license number issued by the State Contractor's Board 024521A  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1442  
 Signed Thomas on Hawk  
 By driller performing actual drilling on site or contractor  
 Date 5-17-99

7. WELL TEST DATA

TEST METHOD	Bailer	Pump	Air Lift	Draw Down (Feet Below Static)	Time (Hours)
<u>STAT</u>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<u>99 MAY 15 10:51</u>	