

195

WHITE-DIVISION OF WATER RESOURCES  
CANARY-CLIENT'S COPY  
PINK-WELL DRILLER'S COPY

STATE OF NEVADA  
DIVISION OF WATER RESOURCES

OFFICE USE ONLY

LKP-18  
PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. 76651  
Permit No.  
Basin 51

NOTICE OF INTENT NO. 30185

1. OWNER Newmont Gold Co. ADDRESS AT WELL LOCATION Gold Quarry pit  
MAILING ADDRESS

2. LOCATION SW 1/4 NW 1/4 Sec. 2 T. 33 N/S R. 51 E Eureka County  
PERMIT NO. Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Clay		0'	40'	40'
Gravel		40'	50'	10'
Clay		50'	180'	130'
Clay and Gravel		180'	240'	60'
Neat Cement 5 bags w-60 3 bags		0	20'	20'
Neat Cement 6 1/2 bags		200'	240'	40'
Sand 31 bags		150'	200'	50'
Neat Cement 1 1/2 bags		147	150'	3'
Abbruto-site 4 bags		50'	147'	97'
Neat Cement 10 bags		0	50'	50'

8. WELL CONSTRUCTION  
Depth Drilled 240 Feet Depth Cased 200 Feet  
HOLE DIAMETER (BIT SIZE)  
From To  
10 3/4 Inches 0 Feet 20 Feet  
6 Inches 20 Feet 240 Feet  
CASING SCHEDULE  
Size O.D. (Inches) Weight/Ft. (Pounds) Wall Thickness (Inches) From (Feet) To (Feet)  
6 5/8 " 4 " wall 0 ' 20 '  
2 " Blank 1/2 " wall +2 160 '  
2 " Screen 1/4 " wall 160 200 '  
Perforations:  
Type perforation Horiz slots  
Size perforation 3" slots  
From 160 feet to 200 feet  
Surface Seal:  Yes  No Seal Type:  
Depth of Seal 50 '  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
Gravel Packed:  Yes  No  
From 150 feet to 200 feet  
9. WATER LEVEL  
Static water level NA feet below land surface  
Artesian flow NA G.P.M. NA P.S.I.  
Water temperature NA °F Quality NA

Date started 4-19- 19 99  
Date completed 4-20- 19 99

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
<u>NA</u>			

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Eklund Drilling Co. Contractor  
Address 605 Union Pacific Way PO Box 2748 Contractor  
Elko, Nevada 89803  
Nevada contractor's license number issued by the State Contractor's Board 0030823  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2100  
Signed Shawn Taylor  
By driller performing actual drilling on site or contractor  
Date 4-25-99