

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

**WELL DRILLER'S REPORT**

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37851

1. Consultant: \_\_\_\_\_  
 OWNER: CDM ENGINEERS & CONSTRUCTORS, INC ADDRESS AT WELL LOCATION: Vista Canyon Group  
 MAILING ADDRESS: 7025 Lonley Lane, Suite 20 Sparks Solvent/Fuel Site Remediation  
Reno, Nevada 89511 South end of Helms Pit & I-80 E, Sparks, NV  
 2. LOCATION: NW 1/4 NW 1/4 Sec. 10 T. 19 N. N/S R. 1020E Washoe County  
 PERMIT NO. P-9 037-030-09 Sparks Subdivision Name \_\_\_\_\_  
 Issued by Water Resources \_\_\_\_\_ Parcel No. \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Brown sand & silt		0	8	8
Brown & brown gray gravel & sand, some cobbles, little silt		8	35	27
Brown clay gravel & sand, some cobbles to thick boulders		35	45	10
Brown sand & gravel		45	100	55
20-40% silty clay, 40% sand, 20-40% gravel increasing silty clay with depth		100	105	5

8. WELL CONSTRUCTION  
 Depth Drilled 105 Feet Depth Cased 105 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 12 1/4 Inches To 0 Feet 105 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6" PVC		sch 80	0	105
Centralizers @ 17', 56', 96', Locking Cap				
4 1/2" PVC end cap reinforced w/bolts @ bottom				

Perforations: factory sawed slots  
 Type perforation \_\_\_\_\_  
 Size perforation 0.03 Stainless Steel wire wrap  
 From 15 feet to 100 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 8 feet  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Bentonite Seal: 8-9 feet/#30 Sand 9-10 feet  
 Gravel Packed:  Yes  No 10-20 Colorado Silica Sand  
 From 10 feet to 105 feet

9. WATER LEVEL  
 Static water level not known feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. not known P.S.I.  
 Water temperature n/k °F Quality not known

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510  
 Nevada contractor's license number 0022549  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 923  
 Division of Water Resources, the on-site driller  
 Signed Edward J. [Signature]  
 By driller performing actual drilling on site or contractor  
 Date July 16, 1999

Date started 6-26-98, 19\_\_\_\_  
 Date completed 7-01-98, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			