

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37851

Consultant: _____

1. OWNER CDM ENGINEERS & CONSTRUCTORS, INC. ADDRESS AT WELL LOCATION Vista Canyon Group
 MAILING ADDRESS 7025 Longley Lane, Suite 20 Sparks Solvent/Fuel Site Remediation
Reno, Nevada 89511 South end of Helms Pit & I-80 E, Sparks, NV

2. LOCATION NW 1/4 NW 1/4 Sec. 10 T. 19 N. N/S R. 20 E. Washoe County
 PERMIT NO. P-10 037-030-09 Sparks
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|--|--------------|------|-----|------------|
| Sandy silty gravel, 40% sand, 40% gravel, 20% silt, brown | | 0 | 9 | 9 |
| Gravelly sand & cobbles, light brown, rounded, 40% sand, 60% gravel, minor silt | | 9 | 96 | 87 |
| Same as above w/20% silty clay, brown, 40% sand, 40% gravel | | 96 | 99 | 3 |
| Boulder 20% Silty clay, 40% sand, 40% cobbles, increasing clay with depth | | 99 | 100 | 1 |
| | | 99 | 105 | 6 |

8. WELL CONSTRUCTION
 Depth Drilled 105 Feet Depth Cased 105 Feet

HOLE DIAMETER (BIT SIZE)
 From 12 1/2 Inches To 0 Feet 105 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---------------------|-------------------------|-------------|-----------|
| 6" PVC | | sch 80 | 0 | 105 |
| Centralizers @ 17', 54', 94'. Locking Cap | | | | |
| 5' w/PVC end cap w/reinforced bolt @ bottom | | | | |

Perforations: factory sawed slot
 Type perforation _____
 Size perforation 0.030 Stainless Steel wire wrap

From 10 feet to 105 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type: _____
 Depth of Seal 8 feet Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal: 8-9 ft./#30 sand 9-10ft.
 Gravel Packed: Yes No 10-20 Colorado Silica
 From 10 feet to 105 feet Sand

Date started 6-22-98, 19____
 Date completed 6-25-99, 19____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|--------|-------------------------------|--------------|
| | | |
| | | |
| | | |
| | | |

9. WATER LEVEL
 Static water level not known feet below land surface
 Artesian flow not known G.P.M. not known P.S.I.
 Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC.
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510 Contractor
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 923
 Division of Water Resources, the on-site driller.
 Signed Edward F. [Signature]
 By driller performing actual drilling on site or contractor
 Date July 16, 1999