WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK MW-8

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77100
Permit No.
Basin 212

NOTICE OF INTENT NO. 19007

1. OWNER 7-11, INC.
MAILING ADDRESS 10220 SW greenburg Road Portland, Oregon 97223
ADDRESS AT WELL LOCATION 600 North Las Vegas Boulevard Las Vegas, Nevada

2. LOCATION SE ¼ SE ¼ Sec. 27 T. 20 S R. 61 E clark County
PERMIT NO. (Issued by Water Resources) Parcel No. 139-27-805-002 Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt surface		0	2"	
gravel Road fill				
Clayey sand, pale		2	7	
yellowish brown,				
damp, medium to				
coarse sand				
Caliche, highly		7	13	
cemented dry,				
yellowish, gray				
Clayey sand, medium		13	20	
light gray, very				
moist, very dense				
coarse, few gravel				
Strong hydrocarbon				
odor				
decreasing gravels				
Sandy clay, medium		26	30	
light gray, very				
moist, trace				
gravel, coarse				
sand, very dense				

Date started 9-8, 1999
Date completed 9-8, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 10 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4			0	10

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 10 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 8
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 8 feet to 30 feet

9. WATER LEVEL
Static water level ~13 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, Inc. (Contractor)
Address 301 West Deer Valley Rd #7 Phoenix, Arizona 85027 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M007071
Signed Danny Gomez (By driller performing actual drilling on site or contractor)
Date 10/28/99

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(D)-627