WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

MW-7

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77102
Permit No.
Basin 212

NOTICE OF INTENT NO. 19007

1. OWNER 7-11, INC
MAILING ADDRESS 10220 SW Greenburg Rd Portland, Oregon 97223
ADDRESS AT WELL LOCATION 600 North Las Vegas Boulevard Las Vegas, Nevada

2. LOCATION SE ¼ SE ¼ Sec. 27 T. 20 ~~N~~ S R. 61 E. Clark County
PERMIT NO. Issued by Water Resources | Parcel No. 139-27-805-002 | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Concrete surface		0	6"	
silty gravel, road fill, dark yellowish orange moist		6"	2	
Sandy clay, coarse, very pale orange, dry, few gravels		2	5	
Sandy clay, well graded coarse sand, yellowish gray, dry, little gravel		5	10	
Caliche, highly cemented, dry yellowish gray		10	18	
Sand, medium gray, wet, medium to coarse, dense, trace clay, some silt, strong hydrocarbon odor		18	24	
Clayey sand, medium gray, wet medium to coarse sand, some gravel, strong hydrocarbon odor		24	30	

Date started 9-8, 1999
Date completed 9-8, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 10 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 Inches	0 Feet	30 Feet	
Inches	Feet	Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4			0	10

Perforations:
Type perforation Sch 40 PVC
Size perforation .020
From 10 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 8
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 8 feet to 30 feet

9. WATER LEVEL
Static water level 18 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name The Verde Companies, Inc. (Contractor)
Address 301 West Deer Valley Rd #7 Phoenix, Arizona 85027 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 41809
Nevada driller's license number issued by the Division of Water Resources, the on-site driller H207071
Signed (By driller performing actual drilling on site or contractor)
Date 10/28/99

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627