WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77147
Permit No.
Basin 49

NOTICE OF INTENT NO. 15798

1. OWNER Al Park
MAILING ADDRESS 1600 Idaho Street
Elko, NV 89801

ADDRESS AT WELL LOCATION 1600 Idaho Street, Elko, NV

2. LOCATION SE 1/4 SW 1/4 Sec. 11 T 34N N/S R 55E E Elko County
PERMIT NO. Issued by Water Resources
001-590-003 Parcel No.
MW-8 Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt/Fill		0	1	1
Sandy clay		1	6	5
Clayey sand		6	8.5	2.5
Sandy silty clay		8.5	10.5	2
Sandy clay		10.5	13.5	3
Clayey sand		13.5	17.5	4
Sandy clay		17.5	23.5	6
Sandy clayey gravel		23.5	28.5	5
Gravelly clay		28.5	32.5	4
Clayey gravel		32.5	37.5	5
Gravel with clay		37.5	48	10.5
Clay with sand		48	49	1

Date started 1/21/1999 , 19__
Date completed 1/21/1999 , 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 49 Feet Depth Cased 49 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	49	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.64	0.157	0	49

Perforations:
Type perforation Factory slot
Size perforation 0.020
From 29 feet to 49 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 24'/24-27' Bentonite
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 27 feet to 49 feet

9. WATER LEVEL
Static water level 38 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Thomas High c/o Converse Consultants
Contractor
Address 731 Pilot Road, Suite H
Contractor
Las Vegas, NV 89119
Nevada contractor's license number issued by the State Contractor's Board 0034757
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1869
Signed
By driller performing actual drilling on-site or contractor
Date 4/7/1999

USE ADDITIONAL SHEETS IF NECESSARY