PZ97-1

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Plugging of dual completions

OFFICE USE ONLY
Log No. 77615
Permit No.
Basin 61

NOTICE OF INTENT NO. 39988

1. OWNER BARRICK GOLDSTRIKE MINES
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINESITE, NORTH OF CARLIN, NV.

2. LOCATION NE ¼ SW ¼ Sec. 30 T 36 N/S R 50 E EUREKA County
PERMIT NO. M/O-441A Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BOTH TUBES ABANDONED BY PUMPING NEAT CEMENT FROM T.D. TO SURFACE. 2" TUBE TOOK 62 CU. FT. OF CEMENT. 1.25" TUBE TOOK 16 CU. FT. OF CEMENT.				
NOTE:				
THE 1.25" TUBE WAS DRY AT THE TIME THE WELL WAS ABANDONED. THE 2" TUBE STATIC WATER LEVEL WAS 1636' BELOW LAND SURFACE.				

Date started AUGUST 4, 1999
Date completed AUGUST 4, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 2010 Feet Depth Cased 2010 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12.25 Inches	0 Feet	175 Feet	
6.50 Inches	175 Feet	1075 Feet	
6.25 Inches	1075 Feet	2010 Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1.25	3.00	0.191	+2	2010
2.00	5.02	0.218	+2	1460
7.00	17.35	0.250	0	175

Perforations:
Type perforation SLOTTED DRILLED
Size perforation 1.25":0.125" 2": 0.094"
From 2": 1990 feet to 2010 feet
From 1.25": 1440 feet to 1460 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1.25": 1428 feet to 1470 feet
2": 1975 2010

9. WATER LEVEL
Static water level SEE NOTES feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address P.O. BOX 5279 (Contractor)
ELKO, NV 89802

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1716

Signed David Haas
By driller performing actual drilling on site or contractor

Date AUGUST 4, 1999

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627

B.S.T.C

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

PZ97-1

STATE OF NEVADA
DIVISION OF WATER RESOURCES

Plugging of dual completion

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77618
Permit No.
Basin 61

NOTICE OF INTENT NO. 39988

1. OWNER BARRICK GOLDSTRIKE MINES
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINESITE, NORTH OF CARLIN, NV.

2. LOCATION NE ¼ SW ¼ Sec. 30 T 36 N/S R 50 E EUREKA County
PERMIT NO. M/O-441A (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BOTH TUBES ABANDONED BY PUMPING NEAT CEMENT FROM T.D. TO SURFACE. 2" TUBE TOOK 62 CU. FT. OF CEMENT. 1.25" TUBE TOOK 16 CU. FT. OF CEMENT.				
NOTE: THE 1.25" TUBE WAS DRY AT THE TIME THE WELL WAS ABANDONED. THE 2" TUBE STATIC WATER LEVEL WAS 1636' BELOW LAND SURFACE.				

Date started AUGUST 4, 1999
Date completed AUGUST 4, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 2010 Feet Depth Cased 2010 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12.25 Inches		0 Feet	175 Feet
6.50 Inches		175 Feet	1075 Feet
6.25 Inches		1075 Feet	2010 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1.25	3.00	0.191	+2	2010
2.00	5.02	0.218	+2	1460
7.00	17.35	0.250	0	175

Perforations:
Type perforation SLOTTED DRILLED
Size perforation 1.25":0.125" 2": 0.094"
From 2": 1990 feet to 2010 feet
From 1.25":1440 feet to 1460 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1.25":1428 feet to 1470 feet
2": 1975 2010

9. WATER LEVEL
Static water level SEE NOTES feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address P.O. BOX 5279 (Contractor)
ELKO, NV 89802

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1716

Signed David Haas
By driller performing actual drilling on site or contractor

Date AUGUST 4, 1999

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

B.St.C