F296-11

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Plugging of Hole Due Compl

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77618
Permit No.
Basin

NOTICE OF INTENT NO. 39977

1. OWNER BARRICK GOLDSTRIKE MINES
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE SITE, NORTH OF CARLIN, NV.

2. LOCATION NW ¼ SE ¼ Sec. 19 T. 36 (N)S R. 50 E. EUREKA County
PERMIT NO. M/O-441A Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BOTH TUBES ABANDON-				
ED BY CEMENTING FROM				
T.D. TO SURFACE:				
1: USED 13.4 CU.				
FT. OF CEMENT.				
2: USED 12.0 CU.				
FT. OF CEMENT.				

RECEIVED 99 JUL 6 PM 1:05 STATE ENGINEER'S OFFICE

Date started JUNE 19, 1999
Date completed JUNE 19, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 900 Feet Depth Cased 895 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
14.75 Inches	0 Feet	20 Feet
6.125 Inches	20 Feet	900 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7.875	24	0.300	+2	20
1:1.75	1.55	0.137	+1	895
2:1.75	1.55	0.137	+1	659

Perforations:
Type perforation MILLED SLOT
Size perforation 0.125
From 1: 835 feet to 895 feet
From 2: 599 feet to 659 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 51
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1: 825 - 900 feet & 2: 591 - 662 feet

9. WATER LEVEL
Static water level 1: 855' 2: DRY feet below land surface
Artesian flow N/A G.P.M. P.S.I.
Water temperature COOL °F Quality FAIR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address P.O. BOX 5279 (Contractor)
ELKO, NV 89802
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1888
Signed DAVID DORIOT David Doriot (By driller performing actual drilling on site or contractor)
Date JUNE 21, 1999

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

B.STC

PZ96-11

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Plugging at Date Completion

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77618
Permit No.
Basin Cal

NOTICE OF INTENT NO. 39977

1. OWNER BARRICK GOLDSTRIKE MINES
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE SITE, NORTH OF CARLIN, NV.

2. LOCATION NW ¼ SE ¼ Sec 19 T 36 (N)/S R 50 E EUREKA County
PERMIT NO. M/O-441A (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BOTH TUBES ABANDONED BY CEMENTING FROM T.D. TO SURFACE:				
1: USED 13.4 CU. FT. OF CEMENT.				
2: USED 12.0 CU. FT. OF CEMENT.				

8. WELL CONSTRUCTION
Depth Drilled 900 Feet Depth Cased 895 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
14.75 Inches	0 Feet	20 Feet
6.125 Inches	20 Feet	900 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7.875	24	0.300	+2	20
1:1.75	1.55	0.137	+1	895
2:1.75	1.55	0.137	+1	659

Perforations:
Type perforation MILLED SLOT
Size perforation 0.125
From 1: 835 feet to 895 feet
From 2: 599 feet to 659 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 51
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1: 825 - 900 feet to 2: 591 - 662 feet

9. WATER LEVEL
Static water level 1: 855' 2: DRY feet below land surface
Artesian flow N/A G.P.M. P.S.I.
Water temperature COOL °F Quality FAIR

Date started JUNE 19, 1999
Date completed JUNE 19, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address P.O. BOX 5279 (Contractor)
ELKO, NV 89802

Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1888

Signed DAVID DORIOT David Doriot (By driller performing actual drilling on site or contractor)
Date JUNE 21, 1999

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (0)-627

BSTV