WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77744
Permit No.
Basin 49

NOTICE OF INTENT NO. 41866 A

1. OWNER PERRY SARGENT
MAILING ADDRESS 137 PINE STREET
ELKO, NV 89801

ADDRESS AT WELL LOCATION SOUTH SIDE OF LOUISIANA

2. LOCATION SE 1/4 NW 1/4 Sec. 7 T 34N N/S R 56E E ELKO County
PERMIT NO. (Issued by Water Resources) 32-005-049 (Parcel No.) LAST CHANCE #3 (Subdivision Name)

3. **WORK PERFORMED**
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. **PROPOSED USE**
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. **WELL TYPE**
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. **LITHOLOGIC LOG**

Material	Water Strata	From	To	Thickness
Well was pumping dry - Static before plugging				
265'				
Perforate 4 slots per foot from 100-360 - casing				
was torch cut perforated from 360-400				
Pump abandonment fluid from 400-20				
Cement from 0-20				
Material used:				
17 bags of abandonite mixed at 40 Gal water/sk				
5 bags of cement				
cut casing off 4' below grade				

Date started 6/30/99 , 19__
Date completed 6/30/99 , 19__

7. **WELL TEST DATA**
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. **WELL CONSTRUCTION**
Depth Drilled 400 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13	.188	+1	310
5		.188	260	400

Perforations:
Type perforation knife cut
Size perforation approx. 1 x 1/4
From 100 feet to 400 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From UNK feet to UNK feet

9. **WATER LEVEL**
Static water level 265 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name HACKWORTH DRILLING, INC (Contractor)
Address P.O.BOX 850 (Contractor)
ELKO,NV 89803
Nevada contractor's license number issued by the State Contractor's Board 020582
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1689
Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 7/10/99

USE ADDITIONAL SHEETS IF NECESSARY