WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 77889
Permit No.
Basin 230

NOTICE OF INTENT NO. 17791

1. OWNER JoAnne Donaldson
MAILING ADDRESS Southside Farm Rd - Beatty Wood - Same
Amargosa Valley NV 89020

ADDRESS AT WELL LOCATION

2. LOCATION ¼ ¼ Sec. 15 T. 16 N/S R. 48 E. Nye County
PERMIT NO. 19-551-62 File Map 413004 Parcel 4
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil + Sand		0	10	10
Sand + Gravel		10	79	69
Cemented Sand	1st	79	123	44
Clay + Gravel		123	148	25
Cemented Sand	2nd	148	156	8
Gravel - little clay		156	160	4
Bottom of hole				160'

Date started November 3, 1999
Date completed November 4, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)
10 5/8 Inches From 0 Feet To 160 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6" PVC				
Surface Protective Casing				
6' of 8" Steel .1808				

Perforations:
Type perforation Machined
Size perforation 3" x 7/8" every 12"
From 140' feet to 160' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 50' feet to 160' feet

9. WATER LEVEL
Static water level 107' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. (Contractor)
Address HC 69 Box 452 (Contractor)
Amargosa Valley, NV 89020
Nevada contractor's license number issued by the State Contractor's Board 5376-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 830
Signed Dave Rose
By driller performing actual drilling on site or contractor
Date November 25, 1999

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627