WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1" Book

OFFICE USE ONLY
Log No. 77891
Permit No.
Basin 230

NOTICE OF INTENT NO. 17790

1. OWNER Brenda Strey
MAILING ADDRESS Brushwood Ave
Amargosa Valley, NV 89020

ADDRESS AT WELL LOCATION Eastern end of Brushwood Ave
Amargosa Valley, NV 89020

2. LOCATION NE ¼ NW ¼ Sec. 15 T. 16 N/S R. 48 E. Nye County

PERMIT NO. ..... Issued by Water Resources | 19-551-20 Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	10	10
Sand w/layers of gravel		10	85	75
Sand + Clay		85	122	37
Gravel w/pads of clay	1st	122	157	35
Cemented Sand		157	169	12
Gravel w/sand	2nd	169	173	4
Sand + gravel w/clay		173	180	7
Bottom of hole				180'

DCNR/DWR Received JAN 14 2000 LAS VEGAS OFFICE

Date started Sept 10, 1999
Date completed Sept 11, 1999

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 180' Feet Depth Cased 180' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0' Feet	180' Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6" PVC				
Surface Protective Casing				
8" of 8" Steel .1808 wall				

Perforations:
Type perforation Machined
Size perforation 3" x 7/8" every 12"
From 160' feet to 180' feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50' feet to 180' feet

9. WATER LEVEL
Static water level 98' feet below land surface
Artesian flow ..... G.P.M. ..... P.S.I.
Water temperature 72 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Cook Drilling Co. Contractor
Address HC 69 Box 452 Contractor
Amargosa Valley, NV 89020

Nevada contractor's license number issued by the State Contractor's Board 5376A

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 830

Signed Dave Rowe
By driller performing actual drilling on site or contractor

Date Original 9-15-99 1-6-00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627