Duplicate Log

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1" Book

OFFICE USE ONLY
Log No. 78013
Permit No.
Basin 230

NOTICE OF INTENT NO. 17800

1. OWNER Lois Lynn
MAILING ADDRESS 6228 Dayton Ave, Las Vegas, NV 89108-2534
ADDRESS AT WELL LOCATION Anvil Rd & Powerline, Amargosa Valley, NV 89020

2. LOCATION NE ¼ NW ¼ Sec. 29 T. 16 N/S R. 49 E. Nye County
PERMIT NO. Issued by Water Resources | Parcel No. 19-171-36 | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Clay		0	74	74
Cemented Sand & gravel		74	106	32
Sand w/ beds of clay	1st	106	146	40
Sand, Clay & gravel		146	154	8
Sand & gravel	2nd	154	176	22
Bottom of Hole				176'

Date started Sept. 26, 1999
Date completed Sept. 27, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 176 Feet Depth Cased 176' Feet

HOLE DIAMETER (BIT SIZE)
10 5/8 Inches From 0 Feet To 176' Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6" PVC			0	176
Surface Protective Casing				
6' of 8" Steel		.1808 Wall	0	6

Perforations:
Type perforation Machined
Size perforation 3" x 7/8" every 12"
From 156 feet to 176 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 50' feet to 176' feet

9. WATER LEVEL
Static water level 110' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 70 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. (Contractor)
Address HC 69 Box 452 (Contractor)
Amargosa Valley, NV 89020
Nevada contractor's license number issued by the State Contractor's Board 5376A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 830
Signed Dave Rowe
By driller performing actual drilling on site or contractor
Date Original 9-29-99 1-6-00

CONFIDENTIAL Received JAN 14 2000 LAS VEGAS OFFICE

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627