WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 78207
Permit No.
Basin 165

NOTICE OF INTENT NO. 43843

1. OWNER Prim Ventures
MAILING ADDRESS P.O. Box 12219
Zepher Cove, NV 89448

ADDRESS AT WELL LOCATION Schneider Ranch

2. LOCATION NE 1/4 NE 1/4 Sec. 9 T 14N N/S R 19E E Douglas County
PERMIT NO. W-516 (Issued by Water Resources) | 15-020-14 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☒ Other Test #1

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Decomposed granite		0	20	
Black & white granite		20	520	
* Pull 20 ft. conductor.				
Install bariod hole plug		520	20	
Install grout mix from		20	surface	
ABANDONMENT				

Date started 12/10/99, 19__
Date completed 12/10/99, 19__

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
80		6 hrs.

8. WELL CONSTRUCTION

Depth Drilled 520 Feet Depth Cased 20 cond. Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7-7/8 Inches		0 Feet	20 Feet
6-1/8 Inches		20 Feet	520 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8		.188	+2	20

Perforations:
Type perforation N/A
Size perforation N/A
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From ____ feet to ____ feet

9. WATER LEVEL

Static water level 30 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed [signature] (By driller performing actual drilling on-site or contractor)

Date 12/7/99