

REPORT NO. 99.67

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

LOG NO. 78216  
PERMIT NO. 105  
BASIN 105  
NOTICE OF INTENT NO. 43170

OWNER Washoe Tribe of Nevada & California  
MAILING ADDRESS PO Box 21510 Carson City, Nevada 89721

ADDRESS OF WELL Hobo Hot Springs  
Douglas, County

2. WELL LOCATION SW 1/4 NW 1/4 SEC. 19 T 14 R 20E E Douglas COUNTY  
PERMIT NO. \_\_\_\_\_ PARCEL NO. 15-060-480 SUBDIVISION NAME \_\_\_\_\_

3. TYPE OF WORK			4. PROPOSED USE			5. WELL TYPE		
<input checked="" type="checkbox"/> New Well	<input type="checkbox"/> Replace	<input type="checkbox"/> Recondition	<input checked="" type="checkbox"/> Domestic	<input type="checkbox"/> Irrigation	<input type="checkbox"/> Test	<input type="checkbox"/> Cable	<input checked="" type="checkbox"/> Rotary	<input type="checkbox"/> RVC
<input type="checkbox"/> Deepen	<input type="checkbox"/> Plug	<input type="checkbox"/> Other	<input type="checkbox"/> Municipal/Industrial	<input type="checkbox"/> Monitor	<input type="checkbox"/> Stock	<input type="checkbox"/> Air	<input checked="" type="checkbox"/> Mud	

6. LITHOLOGIC LOG				
MATERIAL	STRATA	FROM	TO	THICKNESS
Compacted sand & gravel		0	5	5
Sand		5	15	10
Clay, sand & volcanic rock		15	25	10
Clay sand & DG		25	30	5
Heavy brown clay		30	50	20
DG & clay heavy		50	75	25
Sand		75	85	10
Heavy brown clay		85	90	5
Sand & some DG & clay		90	135	45
Heavy brown clay		135	140	5
DG & clay		140	145	5
Heavy brown clay		145	160	15
Clay & sand		160	165	5
Gray clay & rock		165	170	5
Gray clay & small gravel	X	170	190	20
Gray clay & DG		190	198	8

8. WELL CONSTRUCTION			
Depth Drilled	<u>198</u>	Depth Cased	<u>198</u>
HOLE DIAMETER (BIT SIZE)			
<u>10 5/8</u> Inches	<u>0</u> Feet	<u>100</u> Feet	
<u>8 3/4</u> Inches	<u>100</u> Feet	<u>198</u> Feet	
_____ Inches	_____ Feet	_____ Feet	

CASING SCHEDULE				
Size OD	Weight/Ft	Wall Thickness	From	To
<u>6 5/8</u>	<u>12.92</u>	<u>.188</u>	<u>+2</u>	<u>198</u>

PERFORATIONS:

Type Perforation Factory Size Perforation 3/32 x 3

From 158 Feet to 178 Feet

From \_\_\_\_\_ Feet to \_\_\_\_\_ Feet

From \_\_\_\_\_ Feet to \_\_\_\_\_ Feet

SURFACE SEAL:  Yes  No SEAL TYPE:  Neat Cement

Seal Depth 50  Cement Grout

PLACEMENT METHOD:  Pumped  Concrete Grout

Poured

GRAVEL PACKED:  Yes  No

From 50 Feet to 198 Feet

9. WATER LEVEL

Static Water Level 15 Feet Below Land Surface

Artesian Flow \_\_\_\_\_ GPM \_\_\_\_\_ PSI

Water Temperature Cool F Quality Clear

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Aqua Drilling & Well Service, Inc.

Address 675 Edison Way  
Reno, Nevada 89502

NV. CONTRACTOR'S LIC. NO. 15291 DRILLER'S LIC. NO. ON SITE 1981

Signed [Signature]

By driller performing actual drilling on site of contractor

Dated November 16, 1999

Notes :

Date Started 11/2/99 Date Completed 11/4/99

7. WELL TEST DATA			
TEST METHOD	Bailer	Pump	Air Develop
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
GPM	DRAWDOWN	TIME (HRS)	
<u>20+</u>		<u>1.3</u>	