

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 18456  
 Permit No. \_\_\_\_\_  
 Basin 83

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 42496

1. OWNER Canyon GID  
 MAILING ADDRESS 501 Rue de la Blanc Sparks NV 89434  
 ADDRESS AT WELL LOCATION Rainbow Bend - near Lockwood  
 2. LOCATION SE 1/4 SE 1/4 Sec. 17 T 19 R 21 E Storey County  
 PERMIT NO. W-519  
 Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Fill material boulders & clay		0	20	
yellow boulders & clay		20	30	10
green clay & green sandstone		30	80	50
gray volcanic		80	98	18
green claystone		98	120	22
green sandy clay w/s brown volcanic		120	135	15
gray clay w/red volcanic		135	180	45
gray clay w/s volcanic		180	200	20

8. WELL CONSTRUCTION  
 Depth Drilled 200 Feet Depth Cased n/a Feet  
 HOLE DIAMETER (BIT SIZE)  

Inches	From	To
<u>18</u>	<u>0</u>	<u>30</u>
<u>8-1/2</u>	<u>30</u>	<u>200</u>

 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>14</u>		<u>.250</u>	<u>0</u>	<u>30</u>

ABANDONMENT  
 This well was abandon using 4 cyd. of 7 sack grout. Grout pumped from bottom of borehole to surface. 14 inch casing was cut off below ground level.

Perforations:  
 Type perforation n/a  
 Size perforation n/a  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 200  
 Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

9. WATER LEVEL  
 Static water level 12 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature cool °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Humboldt Drilling & Pump Co., Inc. Contractor  
 Address 4675 W. Winnemucca Blvd Contractor  
Winnemucca, Nevada 89445  
 Nevada contractor's license number issued by the State Contractor's Board 015234  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713  
 Signed Jim A. Tomph  
 by driller performing actual drilling on-site or contractor  
 Date 1/15/00

Date started 1/12 2000  
 Date completed 1/13 2000

7. WELL TEST DATA

TEST METHOD:	Bailer		Pump		Air Lift	
	G.P.M.	Draw Down (Feet Below Static)	G.P.M.	Draw Down (Feet Below Static)	G.P.M.	Time (Hours)

RECEIVED  
 00 JAN 19 AM 11:4  
 STATE ENGINEERS OFFICE

