

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 43172  
635 Calle De LaPlata  
Sparks, Nevada

1. OWNER David Galleron ADDRESS AT WELL LOCATION  
 MAILING ADDRESS 2105 Ponderosa Drive  
Sparks, Nevada  
 2. LOCATION SW 1/4 SW 1/4 Sec 17 T 21 N/S R 21 E Washoe County  
 PERMIT NO. 076-310-57 Spanish Springs Area  
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air &  Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Blow sand & DG		0	6	6
Salt & pepper DG		6	45	39
Red Clay & Decomposed rocks & DG		45	65	20
Red & salt & pepper granite		65	115	50
Salt & pepper granite & white clay		115	120	5
Salt & pepper granite with rusty white clay		120	130	10
Salt & pepper granite		130	345	215
Salt & pepper granite & pink & green rock		345	380	35
Red clay & rock & salt & pepper granite		380	420	40
Salt & pepper granite		420	525	115
Light green clay & salt & pepper granite		525	540	15
Salt & pepper granite		540	680	140
Salt & pepper pink granite		680	800	120
Salt & pepper granite & gray granite		800	865	65
Clay DG		865	875	10
Salt & pepper granite		875	896	21

8. WELL CONSTRUCTION  
 Depth Drilled 896 Feet Depth Cased 896 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From To  
10 5/8 Inches 0 Feet 52 Feet  
8 1/2 Inches 52 Feet 418 Feet  
6 1/4 Inches 418 Feet 896 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+2	418
5	9.66	.188	396	896

Perforations: Factory  
 Type perforation  
 Size perforation 3/32 x 3  
 From 378 feet to 398 feet  
 From 556 feet to 596 feet  
 From 836 feet to 876 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 54'  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 54 feet to 418 feet

9. WATER LEVEL  
 Static water level 569 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started November 22 19 99  
 Date completed December 9 19 99

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Pump	2.5-3	250	

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Aqua Drilling & Well Service, Inc. Contractor  
 Address 675 Edison Way  
Reno, Nevada 89502  
 Nevada contractor's license number 15291  
 issued by the State Contractor's Board.  
 Nevada driller's license number issued by the 1981  
 Division of Water Resources, the on-site driller.  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date December 24, 1999