WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 78817
Permit No.
Basin 105

NOTICE OF INTENT NO. 27997

1. OWNER John Daniels
MAILING ADDRESS 5395 Huntley St Unit #7 Seim. Valley Rd 93063
ADDRESS AT WELL LOCATION 2597 old Ranch Rd Gardnerville NV 89410

2. LOCATION NW ¼ NW ¼ Sec. 15 T. 12 N S R. 21 E. Douglas County
PERMIT NO. Issued by Water Resources | Parcel No. 35-350-020 | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden		0	3	3
Brown Hard Pan Clay		3	22	19
Course 1/4 Gravels and Clay		22	48	26
Brown Sandy Clay		48	240	192
Soft Cemented Sands		240	260	20
Small Volcanic Gravels and Sands	X	260	274	14
Brown Clay		274	365	91
Volcanic Sands Very Soft Zone DG Sands	XX	365	378	12
Gray Clay Small Sands Soft.	~~325~~	378	405	18
Blue Gray Cummy Clay		405	410	5

Date started 12-16, 1999
Date completed 12-22, 1999

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
18-20	80	3 HRS

8. WELL CONSTRUCTION
Depth Drilled 410 Feet Depth Cased 410 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 3/4 Inches	0 Feet	410 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.03	.188	0	410

Perforations:
Type perforation Mill Slot
Size perforation 3X3/32
From 350 feet to 370 feet
From 390 feet to 410 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 55 feet to 410 feet

9. WATER LEVEL
Static water level 240 feet below land surface
Artesian flow G.P.M. 18-20 P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Capital City Well Drilling Contractor
Address 20 [illegible] Carson City, NV [illegible] Contractor

Nevada contractor's license number issued by the State Contractor's Board 41775
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1905
Signed Michael L Hack
By driller performing actual drilling on site or contractor
Date 12-22-99

RECEIVED 10 JAN 14 AM 9:01 STATE ENGINEER'S OFFICE

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627