

SOIL BORING AND WELL CONSTRUCTION LOG: MW-6

CLEARWATER GROUP INC.

FIELD LOCATION OF BORING: NOT TO SCALE 	DRILLING CONTRACTOR: West Hazmat	BORING DIAMETER: 6 5/8 inches	CLIENT/LOCATION: Former Alamo Rent A Car, 1120 Terminal Way, Reno NV	
	DRILL RIG OPERATOR: Darren Mora	BORING DEPTH: 25.5 Feet	SCREEN SLOT SIZE: 0.02 inches	DRILLING DATE: 5/08/99
	DRILL RIG TYPE: CME 85	WELL DEPTH: 25 feet	WELL MATERIAL: 2-inch dia. PVC	FILTER PACK: #3 Lonestar Sand
	WELL SEAL: Neat Cement over hydrated bentonite		PLANNED USE: Monitoring	LOGGED BY: Ruary Allan

WELL CONSTRUCTION DETAIL WATER LEVEL DEPTH (FEET)	SAMPLING INTERVAL RECOVERY		OWN READING (PPM)	GRAPHIC LOG OR USCS CODE	SAMPLING METHOD: No Samples Collected	MONITORING INST: N.A.	APPROVED BY: Brian Gwinn, R.G.
	FIRST ENCOUNTERED WATER DEPTH: 13 Feet below grade				DATE: STATIC WATER DEPTH - DATE: 12.23 Feet below TOC - 5/21/99		

DEPTH (FEET)	WELL CONSTRUCTION DETAIL	WATER LEVEL	SAMPLING INTERVAL	SAMPLING RECOVERY	OWN READING (PPM)	GRAPHIC LOG OR USCS CODE	DESCRIPTION
1							Fill Material GRAVEL (GP); granitic and volcanic boulders and cobbles; little silt and sand, silt content increasing with depth.
2							
3							
4							
5							
6							Silty SAND with gravel (SM); multicolored, predominantly coarse grained.
7							
8							
9							
10							
11							
12							Well-graded SAND with gravel (SW); multicolored, subrounded; little silt, trace pyrite flakes.
13							
14							
15							
16							
17							
18							
19							Logging performed by recovery of cuttings.
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							

SOIL BORING AND WELL CONSTRUCTION LOG: MW-5

CLEARWATER GROUP INC.

FIELD LOCATION OF BORING: NOT TO SCALE 		DRILLING CONTRACTOR: West Hazmat	BORING DIAMETER: 6 5/8 inches	CLIENT/LOCATION: Former Alamo Rent A Car, 1120 Terminal Way, Reno NV	
		DRILL RIG OPERATOR: Darren Mora	BORING DEPTH: 25.5 Feet	SCREEN SLOT SIZE: 0.02 inches	DRILLING DATE: 5/05/99 & 5/07/99
		DRILL RIG TYPE: CME 85	WELL DEPTH: 25 feet	WELL MATERIAL: 2-in. PVC	FILTER PACK: #3 Lonestar Sand
		WELL SEAL: Neat Cement over hydrated bentonite		PLANNED USE: Monitoring	LOGGED BY: Ruary Allan
		SAMPLING METHOD: No Samples Collected		MONITORING INST: N.A.	APPROVED BY: Brian Gwinn, R.G.
		FIRST ENCOUNTERED WATER DEPTH: 17 Feet below grade		STATIC WATER DEPTH - DATE: 12.89 Feet below TOC - 5/21/99	

WELL CONSTRUCTION DETAIL	WATER LEVEL	DEPTH (FEET)	SAMPLING		OVM READING (PPM)	GRAPHIC LOG OR USCS CODE	DESCRIPTION	
			INTERVAL	RECOVERY				
		1					Fill Material.	
		2						
		3						
		4						Poorly graded GRAVEL (GP); granitic and volcanic coarse grained gravel, boulders and cobbles; little silt and sand.
		5						
		6						
		7						
		8						
		9						
		10						
		11						
		12						
		13						
		14						
		15						Well-graded GRAVEL with sand (GW); multicolored, granitic and volcanic gravel; some well graded sand, boulders and cobbles; little silt; wet.
		16						
		17						
		18						
		19						Well-graded SAND with gravel (SW); multicolored; little silt; wet.
		20						
		21						
		22						
		23						
		24						
		25						Logging performed by recovery of cuttings.
		26						
		27						
		28						
		29						
		30						