WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79067
Permit No.
Basin 87

NOTICE OF INTENT NO. 42915

1. OWNER Airport Authority of Washoe Cy.
MAILING ADDRESS P.O. Box 12490
Reno, NV. 89510

ADDRESS AT WELL LOCATION
Airport Maintainence Facility
Air Gurd Way, Reno, NV.

2. LOCATION NE ¼ SE ¼ Sec. 19 T 19 N/S R 20 E Washoe County

PERMIT NO. | Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Monitor wells #1,2,3,4 and 5 were 2", pvc, wells all constructed with 5' of blank casing on top with 20'/5' of screen on bottom. We mixed and pumped 5 bags of Portland type II cement and approx. 30 gallons of water to fill the 2" wells.				
RW-1 (recovery well) was a 6" pvc well constructed with 5' of blank and 20'/5' of screen. This well required approx 4.5 cubic feet of neat cement.				

MW	SWL	Depth	Size	Blank	Screen
1	7.56	20.5'	2"	5'	20'
2	7.59'	20.38	2"	5'	20'
3	7.61'	20.45'	2"	5'	20'
4	7.64'	20.36'	2'	5'	20'
5	7.69'	20.45'	2"	5'	20'
RW 1	7.65'	20.5'	6"	5'	20'

See attached site map and well const. logs

Date started 11-9, 19 99
Date completed 11-9, 19 99

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation slotted
Size perforation .020
From 5' feet to 20' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal
Placement Method: ☒ Pumped ☐ Poured

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 7.56 to 7.7' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Carson Pump (Contractor)
Address 1401 North Roop St. (Contractor)
Carson City, NV. 89701

Nevada contractor's license number issued by the State Contractor's Board 39920

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1482

Signed Dan Trampe (By driller performing actual drilling on site or contractor)

Date November 11, 1999

RECEIVED 99 NOV 18 AM 11:44 STATE ENGINEER'S OFFICE

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627