283

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 79209
Permit No.
Basin 79

NOTICE OF INTENT NO. 40851

1. OWNER Al Park Petroleum Inc.
MAILING ADDRESS 1600 Idaho Street Elko, Nev. 89803 PO Box 1600
ADDRESS AT WELL LOCATION CONOCO 1600 IDAHO ; ELKO, NV

2. LOCATION SE ¼ SW ¼ Sec. 11 T. 34 N/S R. 55 E. ELKO County
PERMIT NO. N/A Issued by Water Resources
001-590-003 Parcel No.
N/A Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
brown clayey sand (SC) w/ gravels medium dense slightly moist.		0.0	18.0	18.0
brown clay (CH) w/ sand gravel stiff moist		18.0	24.0	6.0
brown clayey gravels (GC) w/ sand dense, moist		24.0	29.0	5.0
brown clayey sand (SC) w/ gravels dense moist (smell of petroleum)	35.0	29.0	34.0	5.0
brown clay (CH) w/ gravels stiff moist		34.0	59.0	25.0

Date started January 18th 2000, 19—
Date completed January 19th 2000, 19—

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 59.0' Feet Depth Cased 54.0' Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
7 3/4	0.0	59.0'

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.70/ft	0.308	54.0	0.0

Perforations:
Type perforation slotted
Size perforation 0.020
From 54.0 feet to 54.0 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 10'-0'
Placement Method: ☐ Pumped ☒ Poured (bentonite 10-13')
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
~~Gravel~~ Sand #16 Packed: ☒ Yes ☐ No
From 13.0 feet to 59.0 feet

9. WATER LEVEL
Static water level 35.0 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Dale Lehman w/ Pezonella Assoc. Contractor
Address 520 Edison Way Contractor
Reno, NV 89502
Nevada contractor's license number issued by the State Contractor's Board N/A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1976
Signed Dale Lehman
By driller performing actual drilling on site or contractor
Date 1/21/00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627