WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80003
Permit No.
Basin 6 pg1

NOTICE OF INTENT NO. 43795

1. OWNER Winnemucca Farms
MAILING ADDRESS P.O. Box 130
Winnemucca, NV 89446

ADDRESS AT WELL LOCATION

2. LOCATION NE 1/4 NE 1/4 Sec. 26 T 38N N/S R 38E E Humboldt County
PERMIT NO. 31141,31142,34006 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [X] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [X] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
silty sand w/little clay		0	62	
sm. sand & gravel		62	65	3
clay		65	70	5
sand & gravel		70	87	17
clay		87	91	4
sand & gravel		91	108	17
cemented sand w/gravel		108	128	20
sand & gravel		128	145	17
cemented sand w/gravel		145	155	10
sand & gravel		155	165	10
sand & gravel w/clay		165	172	7
sand & gravel		172	185	13
br. clay		185	192	7
sand & gravel		192	195	3
sand,gravel w/streaks of clay		195	231	36
sand/cemented sand w/streak of clay		231	254	23
coarse sand		254	259	5
sand w/clay		259	268	9
coarse sand-sm. gravel		268	297	29
coarse sand w/small gravel & little clay		297	304	7
coarse sand/some clay		304	335	31

Continued on next page - 2

Date started 3/16/00 , 19__
Date completed 3/21/00 , 19__

7. WELL TEST DATA

TEST METHOD: [ ] Bailer [X] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
2500	128	7 hrs

pumping level 271 ft.

8. WELL CONSTRUCTION
Depth Drilled 713 Feet Depth Cased 690 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
28 Inches	0 Feet	713 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
18		3/8	0	200
18		3/8	250	280
18		3/8	310	340

Continue Pg 2

Perforations:
Type perforation Johnson screen
Size perforation .100 slot
From 200 feet to 250 feet
From 280 feet to 310 feet
From 340 feet to 400 feet
From 420 feet to 440 feet
From 500 feet to 520 feet

Continue Pg 2.

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 713 feet

9. WATER LEVEL
Static water level 145.15 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1572

Signed [signature] (By driller performing actual drilling on-site or contractor)

Date 3/28/00

WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80003
Permit No.
Basin 69 pg2

Page 2

NOTICE OF INTENT NO. 43795

1. OWNER Winnemucca Farms
MAILING ADDRESS P.O. Box 130
Winnemucca, NV 89446

ADDRESS AT WELL LOCATION

2. LOCATION NE 1/4 NE 1/4 Sec. 26 T 38N N/S R 38E E Humboldt County
PERMIT NO. 31141,31142,34006 (Issued by Water Resources) Parcel No. Subdivision Name

3. **WORK PERFORMED**
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. **PROPOSED USE**
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. **WELL TYPE**
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. **LITHOLOGIC LOG**

Material	Water Strata	From	To	Thickness
clay w/streaks of cement				
sand		335	363	28
sand & gravel		363	374	11
clay/cemented sand layers		374	528	154
coarse sand w/clay		528	545	17
cemented sand w/little clay		545	550	5
sand		550	580	30
sand w/little clay		580	585	5
coarse sand w/clay		585	590	5
clay		590	593	3
sand w/little white clay		593	597	4
sand/clay w/white clay		597	605	8
sand/brown clay		605	607	2
sand		607	613	6
sand/clay		613	620	7
coarse sand/clay		620	645	25
sand		645	653	8
sand/gravel/little clay		653	663	10
sand/little clay		663	665	2
sand/white clay		665	667	2
sand		667	673	6
sand/clay		673	680	7
clay		680	685	5
sandy clay		685	700	15
Continued on next page - 3				

Date started 3/16/00, 19__
Date completed 3/21/00, 19__

7. **WELL TEST DATA**
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. **WELL CONSTRUCTION**
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
18"		318	400	420
18"		318	440	500
18"		318	520	540
18"		318	620	640
18"		318	680	690

Perforations:
Type perforation
Size perforation
From 540 feet to 620 feet
From 640 feet to 680 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. **WATER LEVEL**
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1572

Signed
By driller performing actual drilling on-site or contractor

Date 3/28/00

WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80003
Permit No.
Basin

Page 3

NOTICE OF INTENT NO. 43795

1. OWNER Winnemucca Farms
MAILING ADDRESS P.O. Box 130
Winnemucca, NV 89446

ADDRESS AT WELL LOCATION

2. LOCATION NE 1/4 NE 1/4 Sec. 26 T 38N N/S R 38E E Humboldt County
PERMIT NO. 31141,31142,34006 Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
sand w/cemented sand		700	706	6
sand/clay		706	713	7

Date started 3/16/00, 19__
Date completed 3/21/00, 19__

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION

Depth Drilled _____ Feet Depth Cased _____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured

Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL

Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1572

Signed
By driller performing actual drilling on-site or contractor

Date 3/28/00