WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80281
Permit No. 83
Basin

NOTICE OF INTENT NO. 31071

1. OWNER Gabriel R. Venegas
MAILING ADDRESS P.O. Box 20022
Carson City, NV 89721-0022

ADDRESS AT WELL LOCATION 1900 Empire Rd
Reno, NV 89511

2. LOCATION SE ¼ NE ¼ Sec. 5 T. 17 N/S R. 21 E. STORIE County
PERMIT NO. (Issued by Water Resources) 3-121-07 (Parcel No.) HIGHLANDS (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy, silty loam w/clay		0	2.0	2.0
Clay, light brown & dry w/relic feldspars		2.0	5.0	3.0
Andesite - grey in color competent rock		5.0	42.0	37.0
Andesite - minor alterations (purple color) mafic minerals rotting out (oxidized), some feldspars are "argilized" minor clay in fracture zones.	42.0	42.0	62.0	20.0
Andesite - mostly "fresh" unaltered rock, grey in color with some small zones of minor alteration (secondary mineralizations) with colors of purple & green competent rock to total depth.		62.0	180.0	

Date started 6-13-, 19 2000
Date completed 6-14, 2000

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
40+		

8. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	60	Feet
9	Inches	60	Feet	180	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	2+	180

Perforations:
Type perforation MILLED SLOT
Size perforation 1/8"
From 80 feet to 100 feet
From 140 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 60
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 60 feet to 180 feet

9. WATER LEVEL
Static water level 32 feet below land surface
Artesian flow NO G.P.M. P.S.I.
Water temperature COOL °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) POINTS WEST Drilling
Address (Contractor) P.O. Box 178
WEST POINT, CA 95255
Nevada contractor's license number issued by the State Contractor's Board 39825
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1974
Signed Jimmy L. Delp
(By driller performing actual drilling on site or contractor)
Date 7-1-2000

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627