WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80440
Permit No.
Basin 80B

NOTICE OF INTENT NO. [illegible]

1. OWNER Frehner Construction
MAILING ADDRESS 124 W. Brooks
Las Vegas, NV 89030

ADDRESS AT WELL LOCATION Hwy 40, Quinn River/Denio Well

2. LOCATION NE 1/4 SW 1/4 Sec. 33 T 42N N/S R 33E E Humboldt County
PERMIT NO. Waiver W-C-202 Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravel		0	35	
grey clay		35	90	55
sand & pea gravel		90	125	35
green clay		125	130	5
tan clay		130	165	35
gravel & clay		165	175	10
tan clay		175	205	30
gravel & clay		205	210	5
clay		210	265	55
brown clay		265	270	5
clay		270	325	55
dark brown shale		325	335	10
white clay		335	337	2
brown shale		337	355	18
clay		355	365	10
shale		365	375	10
grey clay		375	390	15
brown shale		390	460	70
ABANDONMENT				
Pumped borehole with				
cement grout from 460				
ft. to surface		0	460	460

Date started 6/3/00, 19__
Date completed 6/6/00, 19__

7. WELL TEST DATA
TEST METHOD [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

RECEIVED 00 JUN 21 AM 11:38 STATE ENGINEER'S OFFICE

8. WELL CONSTRUCTION
Depth Drilled 460 Feet Depth Cased 0 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9-7/8 Inches	0 Feet	460 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
n/a		n/a	n/a	n/a

Perforations:
Type perforation n/a
Size perforation n/a
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 460
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 80 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. Contractor
Address 4675 W. Winnemucca Blvd Contractor
Winnemucca, Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed [signature] By driller performing actual drilling on-site or contractor
Date 6/20/00